

INSTALLATION GUIDE

DI 005 EN H

LPG-TRONIC

Described in EC-type examination certificate N°: LNE-13621

H	2018/02/12	Integration of the ASKW remote control, new version of the control box [MDV545]	DSM/CHR	FDS/MV
Issue	Date	Nature of modifications	Written by	Approved by

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY				
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION				
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC			Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr			Page 1 / 49

CONTENTS

1. GENERAL RECOMMENDATIONS	3
1.1. MECHANICAL RECOMMENDATIONS	3
1.2. ELECTRICAL RECOMMENDATIONS	4
1.3. PNEUMATIC RECOMMENDATIONS	6
2. GENERAL PRESENTATION	7
2.1. USE ACCORDING TO MID CERTIFICATE	7
2.2. SPECIAL CONDITIONS FOR INSTALLATION IN ANY CASES	7
3. PART LIST	7
4. INSTALLATION AND SEALING DRAWING OF THE LPG-TRONIC	9
5. CALCULATOR-INDICATOR MICROCOMPT+	10
5.1. INSTALLATION RECOMMENDATIONS CALCULATOR-INDICATOR MICROCOMPT+	11
5.2. ELECTRICAL WIRING CALCULATOR-INDICATOR MICROCOMPT+: BASIC VERSION	12
Terminal assignment of the MICROCOMPT+ power supply board basic version	13
5.3. ELECTRICAL WIRING WITH CONTROL BOX AND RCT4 REMOTE CONTROL	15
Terminal assignment of the MICROCOMPT+ power supply board RCT4 version	16
Control box LPG-TRONIC	17
Electrical wiring control box RCT4 version	19
Pneumatic wiring control box RCT4 version	21
Remote control RCT4	22
Electrical wiring RCT4 remote control receiver	23
5.4. ELECTRICAL WIRING WITH CONTROL BOX AND RC LYNX REMOTE CONTROL	24
Terminal assignment of the MICROCOMPT+ power supply board RC LYNX version	25
Control box LPG-TRONIC	27
Electrical wiring control box RC LYNX version	29
Pneumatic wiring control box RC LYNX version	31
5.5. ELECTRICAL WIRING WITH CONTROL BOX AND ASKW REMOTE CONTROL	32
Terminal assignment of the MICROCOMPT+ power supply board ASKW version	33
Control box LPG-TRONIC	34
Electrical wiring control box ASKW version	36
Electrical wiring ASKW remote control receiver/PLC	38
Pneumatic wiring control box ASKW version	41
6. METERING LINE GPL-BALC	42
6.1. INSTALLATION AND SEALING RECOMMENDATIONS ADRIANE TURBINE METER	43
7. PRINTER	44
7.1. INSTALLATION RECOMMENDATIONS PRINTER	45
8. CONVERTER 24VDC/24VDC 2.1A 50W	46
9. TEMPERATURE PROBE PT100 – CT1001	47
9.1. INSTALLATION RECOMMENDATIONS TEMPERATURE PROBE	48
10. KIT FOR MEASURING SYSTEM IDENTIFICATION PLATE	49

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 2 / 49

1. GENERAL RECOMMENDATIONS

IN ORDER TO AVOID ALL THE PROBLEMS CONCERNING THE INSTALLATION, THE OPERATION AND THE MAINTENANCE OF THE EQUIPMENTS, BEING ABLE TO CREATE INOPPORTUNE FAILURE, PLEASE RESPECT THE FOLLOWING RECOMMENDATIONS.

BEFORE ANY WORK, MAKE SURE THAT THE EQUIPMENTS ARE NOT POWERED.


1.1. MECANICAL RECOMMENDATIONS

- ⇒ Respect the recommendations of the instruction manual specifying the installation, operation and maintenance conditions of the ATEX equipment (instruction manual supplied with the equipment).
- ⇒ Take care to place the equipment in order to facilitate their installation, operation and maintenance by the technicians (working ergonomics).
- ⇒ Take care to position properly the equipment; the display must be readable without any difficulty.
- ⇒ Apply a tightening torque suitable with size and material of the fixation element except particular specifications mentioned on the presentation drawing or in the installation guides.
- ⇒ Mechanically protect the cables with the corrugated conduit if the cables are not ADR (corrugated conduit adapted to vehicles used for "carriage of dangerous goods of road" - hydrocarbons, LPG ... - and meet the requirements of French standard NF R13-903).
- ⇒ Ensure there are a good mechanical strength and a good sealing between cable glands and cables, and between cable glands and corrugated conduit.
- ⇒ Respect cables and corrugated conduit radii of curvature.
- ⇒ Leave enough flexibility to wires in order to avoid any risk of stripping.
- ⇒ Allow the drainage of the water in the lower loop (siphon) of the corrugated conduit (not water retention inside the corrugated conduit).

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 3 / 49

1.2. ELECTRICAL RECOMMENDATIONS

- ⇒ Respect the recommendations of the instruction manual specifying the installation, operation and maintenance conditions of the ATEX equipment (instruction manual supplied with the equipment).
- ⇒ Connect the supply of the equipment downstream cut-out, on the power supply reserved to the measured distribution.
- ⇒ Put a delayed protection of 5A upstream the 24VDC supply to protect equipment in case of reverse polarity or overcurrent.
- ⇒ Use ADR specific cable, if it is not the case, use at minimum a cable resisting to hydrocarbons. Mechanically protect this cable with a corrugated conduit (corrugated conduit adapted to vehicles used for "carriage of dangerous goods by road" - hydrocarbons, LPG ... - and meet the requirements of French standard NF R13-903).
- ⇒ Take care not to damage the terminals of the different electronic boards while wiring.
 - Screw terminals: do not damage the screw heads of the terminals.
 - Use insulated lugs and insulated wire ferrules adapted to the section of wires.
 - Spring terminals: do not block the springs (if a spring is blocked, the electronic board must be replaced).
 - Use flat screwdriver 0.4x2.5 (see fig.1).
 - Insert the screwdriver slightly tilted, then push it perpendicularly to the terminal.
 - Do not exceed the upright position when the screwdriver is down in order not to block the spring.
 - Insert or remove the wire and remove the screwdriver.
- ⇒ Pass the power supply cores (24VDC truck) through the ferrites by carrying out a loop (ALMA supply).
- ⇒ Do not use wires of section higher than 1.5mm².
- ⇒ Do not insert more than two wires in a terminal, if necessary use an insulated twin wire ferrule (unless otherwise indicated).
- ⇒ Strictly respect the polarities of the input/output when wiring, in accordance with serigraphy on the cards and/or with the installation guide indications.
- ⇒ Whenever possible, perform a wired test, after wiring and before powering.
- ⇒ Whenever possible, respect the locations of the cables specified in the installation guide.
- ⇒ Equipment must be connected to the frame ground (external ground connection).
- ⇒ Whenever possible, use shielded cables with a 360° connection through the metal cable glands (see the documentation delivered with the equipment).
Otherwise, connect the shields to devices inside the equipment (ground terminal, earth bar, earth boss...).
- ⇒ Whenever possible, label the cables and cores according to the installation guide to facilitate the later maintenance operations.
- ⇒ Respect a homogeneous wire color code.



ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 4 / 49

⇒ Printer TMU295: before positioning the printer on its support, check that configuration switches of the data link protocol, located under the printer, are well positioned: No3 on 'ON' and the 7 others on 'OFF'.

⇒ Current of the electrical devices:

Electrical devices	Supply voltage	Minimum current	Maximum current
MICROCOMPT+	24VDC +/-10%	0.7 A	1.5 A
PRINTER	24VDC +/-10%	0.1 A	5.5 A (switch-on)

⇒ Color code according to DIN 47100.

⇒ Code for designation of colours according to IEC 60757 (except FR codes):

FR				EN	IT	ES	DE
Couleurs	Codes		Standard codes CEI 60757	Colours	Colori	Colores	Farbe
Blanc	Bc		WH	White	Bianco	Blanco	Weiß
Marron	Mr		BN	Brown	Marrone	Marrón	Braun
Vert	Vt		GN	Green	Verde	Verde	Grün
Jaune	Jn		YE	Yellow	Giallo	Amarillo	Gelb
Gris	Gr		GY	Grey	Grigio	Gris	Grau
Rose	Rs		PK	Pink	Rosa	Rosa	Lila
Bleu	Bl		BU	Blue	Blu	Azul	Blau
Rouge	Rg		RD	Red	Rosso	Rojo	Rot
Noir	Nr		BK	Black	Nero	Negro	Schwarz
Violet	Vi		VL	Violet	Viola	Violeta	Violett
Orange	Or		OG	Orange	Arancio	Naranja	Orange
Vert/Jaune	V/J		GYE	Green/Yellow	Verde/Giallo	Verde/Amarillo	Grün/Gelb

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H LPG-TRONIC

This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

Page 5 / 49

1.3. PNEUMATIC RECOMMENDATIONS

- ⇒ Air must be filtered – from 40 to 20µm. Specific recommendations may be added in the installation guides or on the presentation drawings.
- ⇒ The air lubrication must be permanent and correct to avoid any damage on the pneumatic components.
- ⇒ The air supply pressure to the inlet of the equipment must be at least 6 bar and max 8 bar. Specific recommendations may be added in the installation guides or on the presentation drawings.
- ⇒ The pneumatic supply pipes (6/4) must be cut straight (no slanting cut) and should not be crushed after cutting to prevent leakage on fittings.
- ⇒ Respect the radii of curvature of the pneumatic pipes indicated by the manufacturer.
- ⇒ Use colored pneumatic pipes to ease maintenance operation.
- ⇒ In no case the exhaust holes of the pneumatic organs should be plugged, obstructed, unless if that is clearly specified in the installation guides or on presentation drawings.
- ⇒ The use of muffler is not allowed under any circumstances (fouling, frost...). Put a pneumatic pipe of sufficient length, pointed downwards, so that its end is placed in a protected area (L = 100 mm min.).
- ⇒ Pressure unit conversion:

PRESSURE UNIT CONVERSION				
Unités	Bar	PSI	Pascal	kg/cm ²
1 Bar =	1	14,5	100 000 (1x10 ⁵)	1,0197
1 PSI =	0.069	1	6894,5	0,07031
1 Pascal =	1x10 ⁻⁵	14,5x10 ⁻⁵	1	1,0197x10 ⁻⁵
1 kg/cm ² =	0,98	14,22	98066,5	1

PSI = Pound per Square Inch (livre par pouce carré)

1 bar = 100 kPa = 0.1 MPa (1 MPa = 10 bar)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 6 / 49

2. GENERAL PRESENTATION

2.1. USE ACCORDING TO MID CERTIFICATE

The LPG TRONIC measuring system is covered by the EC type examination certificate N° LNE-13621. Refer to this certificate for any precision about its installation.

For the sealing plan, see Annex to EC type examination certificate N° LNE-13621.

2.2. SPECIAL CONDITIONS FOR INSTALLATION IN ANY CASES

- ⇒ Safety valves may be incorporated in the ALMA LPG-TRONIC measuring system. If they are located downstream of the turbine meter, they must open to the atmosphere or be connected to the receiving tank. In no case may safety valves located upstream of the turbine meter be connected to the valves located downstream by pipes that bypass the turbine meter.
- ⇒ To prevent any hydraulic connection of bottle under pressure, the purge below the gas separator must finish on a smooth stiff pipe, without threading nor join, and which is not take down.

3. PART LIST

EQUIPMENTS INCLUDED IN THE MEASURING SYSTEM DELIVERED BY ALMA				
Item	Equipment	Designation	Qty	Option*
1		CALCULATOR INDICATOR MICROCOMPT+ LPG TRONIC (Provided with a magnetic or RFID supervisor key)	1	
2		GPL TRONIC CONTROL BOX (Provided with RS232-serial link and power supply for printer)	1	●
3	3.a 	METERING LINE GPL-BALC (Gas separator – ADRIANE turbine meter DN50-30 – differential valve)	1	
	3.b 	ADRIANE TURBINE METER DN50-30 BALC		

Non-contractual pictures

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 7 / 49

EQUIPMENTS INCLUDED IN THE MEASURING SYSTEM DELIVERED BY ALMA

Item	Equipment	Designation	Qty	Option*
4	4a 	PRINTER TMU-295 (Printer – printer holder – cable 5 or 10m)	1	
	4b 	CONVERTER 24VDC/24VDC 2.1A 50W Provided if there is no control box (With RS232 serial link wire and 24VDC power supply for printer)	1	●
5		REMOTE CONTROL RCT4	1	●
6		Pt100 TEMPERATURE SENSOR – CT1001-Pe (Supplied with thermowell)	1	
7		KIT FOR MEASURING SYSTEM IDENTIFICATION PLATE (Plate and sealing device)	1	●
Option*: equipment sold as an option by ALMA, it must be installed on the measuring system if required by the certificate.				

Non-contractual pictures

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H **LPG-TRONIC**

This document is available at www.alma-alma.fr
Units of measure:
 Length: mm
 Angle: degree (° ' ")
 Temperature: °C

Page 8 / 49

5. CALCULATOR-INDICATOR MICROCOMPT+



Document available on website alma-alma.fr

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN H LPG-TRONIC

This document is available at www.alma-alma.fr


Units of measure:
 Length: mm
 Angle: degree (° '' ''')
 Temperature: °C

5.1. INSTALLATION RECOMMENDATIONS CALCULATOR-INDICATOR MICROCOMPT+


- Fasten the box with 4 M6 screws (holder suitable for vibrations and designed to support the MICROCOMPT). On the box: 4 M6 blind holes tapped length=12 over 185x132).
- Leave an open space around the box in order:
 - o To facilitate maintenance operation.
 - o To prevent any pressing on pushbuttons and on the glass.
- The space between the front face of the box and the cabinet door shall be sufficient.
- Dimensions: $A > 100\text{mm}$ and $B > 60\text{mm}$



- SOLUTION 1: straight box if it's a breast height.




Left hand view
Closed box



Left hand view
open box

- SOLUTION 2: 20° angle if it's not at breast height.



Left hand view
Closed box



Left hand view
open box

REFER TO THE INSTRUCTION MANUAL
(DELIVERED WITH THE EQUIPMENT OR AVAILABLE ON ALMA WEBSITE)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN H
LPG-TRONIC

This document is available at www.alma-alma.fr


Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

5.2. ELECTRICAL WIRING CALCULATOR-INDICATOR MICROCOMPT+: BASIC VERSION




ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° / °) Temperature: °C
	This document is available at www.alma-alma.fr	Page 12 / 49

Wiring diagram of the 24Vdc/24Vdc converter for printer:



ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° '' ''') Temperature: °C
	This document is available at www.alma-alma.fr	Page 14 / 49

5.3. ELECTRICAL WIRING WITH CONTROL BOX AND RCT4 REMOTE CONTROL




ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 15 / 49

Terminal assignment of the MICROCOMPT+ power supply board RCT4 version

Any mass braids and shielding must be connected to the MICROCOMPT+ ground bar

TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

MICROCOMPT+ POWER SUPPLY BOARD



EQUIPMENTS CONNECTED TO THE MICROCOMPT+							MICROCOMPT+ POWER SUPPLY BOARD			
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function	Observation
		No.	CG*	Alma	Type					
	CONTROL BOX serial links	C6		●	ADR 12x0.34 sh.	Rx	Vt	1	Tx	PRINTER
						Tx	Jn	2	Rx	
						0V	Nr	3	0V	
						Rx	Bl	4	Tx	RS232 EC + RC
						Tx	Rg/Bl	5	Rx	
						RS485+	Bc	9	RS485+	Serial link RS485 Embedded computing (EC) Remote control (RC)
						RS485-	Rs	10	RS485-	
						Pulses output +	Rg	22	S	
						Pulses output -	Gr	24	0V	PULSES OUTPUT
	TURBINE TRANSMITTER	C3	1/2"NPT		ADR 4x0.34 sh.	12V	Jn	11	12V	TURBINE INPUT
						V1	Mr	12	V1	
						V2	Vt	13	V2	
						0V	Bc	14	0V	
	RECEIVER RCT4 Commands	C5		●	12G1	24VDC	1	25	24VDC	POWER SUPPLY 24VDC
						0V	2	26	0V	
						HS	3	74	24VDC	HIGH SPEED
						Author.	4	75	24VDC	AUTHOR.
						Interm. stop	5	49	24VDC	INTERM. STOP
						Measuring end	6	50	24VDC	MEASURING END
	Pt1000 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100
						-	Bc	34	-	
						-	Vt	35	-	

*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY


THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H LPG-TRONIC


This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C



Electrical wiring control box RCT4 version

Wiring diagram of the control box RCT4 version:



Configuration of switches:

	Linear switching element for relays NC or NO contact	Three-position switch for common contact: 1→24VDC 2→GND (0V) 3→CS (Free contact)
--	---	--

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° '' ''') Temperature: °C
	This document is available at www.alma-alma.fr	Page 19 / 49

TERMINAL ASSIGNMENT OF THE CONTROL BOX RCT4 VERSION



EQUIPMENT CONNECTED TO THE CONTROL BOX													
Option	Equipement	Cable for information)				Function	Colour or No.	Block	Terminal	Function	Observation		
		N°	CG*	Alma	Type								
	MICROCOMPT+ Serial links	C6			12x0.34 sh	Tx	Vt	BN1	1	Rx	PRINTER	RS485 serial link Embedded computing (EC) Remote control (RC)	
						Rx	Jn		2	Tx			
						0V	Nr		3	0V			
						RS485 -	Rs		4	RS485	EC + RC		RS232 serial link Embedded computing (EC) Remote control (RC)
						RS485 +	Bc		5				
						Tx	Bl		10	RS232	EC + RC		
						Rx	Rg/Bl		11				
	PRINTER	C1		●	2x1	Rx	Vt	BN2	1	Rx	PRINTER		
						Tx	Jn		2	Tx			
						0V	Mr		3	0V			
						24VDC	Bc		4	24VDC			
	POWER SUPPLY					24VDC		BN3 - Bornier client	1	24VDC	POWER SUPPLY	24VDC truck battery (after battery switch and protected by a fuse)	
	RC LYNX BELL					0V			2	0V			
	MOTOR STOP								5	-	-		
									6	24VDC/0V/CS	MOTOR STOP	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact	
	PTO								7	CS			
									8	24VDC/0V/CS	PTO	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact	
	HIGH SPEED								9	CS			
									10	24VDC/0V/CS	HIGH SPEED	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact	
									11	CS			
	TRUCK TRUNK								12	-	-		
									13	24VDC/0V/CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact	
									14	CS	TRUCK TRUNK		
	RECEIVER RCT4	C7		●	12G1	24VDC	10		BN3	3	24VDC	SUPPLY CARD AND CRADLE	Power supply for the remote control card and cradle
						0V	11			4	0V		
						24VDC	1	BN4	1	24VDC	MICROCOMPT+ POWER SUPPLY	Fuse	
						0V	2		2	0V			
						Author.	4		4	EV 3/2NC	AUTHOR.	Authorisation	
						HS	5		5	RELAY	HS	High speed	
						PTO	6		6	EV 3/2NC	PTO	Power take off	
						Stop	7		7	RELAY	MS	Motor Stop	
						DC	8		8	EV 3/2NC	DC	Declutching (or High Speed)	
						FV	9		9	EV 3/2NC	FV	Footvalve	
						Security	3		BN5	3	RELAY	SECURITY	Safety request
		V/J											

*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H LPG-TRONIC

This document is available at www.alma-alma.fr


Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

Diagram illustrating the hydraulic system components and their functions:

- Alimentation MS* / *MS air supply** (8 bar max)
- Echappement / *Exhaust*
- Entrée signal ARU / *Emergency stop* (8 bar max)
- Entrée coffre camion / *Trunk* (8 bar max)
- Sortie MS* (Master Switch)
- Sortie ARU* (Arrêt d'urgence / *Emergency stop*)
- Sortie DB (Débrayage) / *Declutching* ou GV (Grande Vitesse) pour camion citerne / *High speed*
- Voyant pneumatique vert (signale la présence du frein parc)
- Frein parc / *parking break* (8 bar max)
- Sortie CF (Clapet de Fond) / *foot valve*
- Sortie PTO (Prise de Mouvement) ou autorisation (commande hydraulique) / *Autori./PTO*
- Alimentation air / *air supply* (8 bar max)
- Régulateur de pression taré à 6 bar (livré avec réducteur et raccord Ø4)

Label	Input	Output	Function	Observation
Air supply	X		Main supply of the control box + detector for pressure drop	Pressure >1 bar: green warning light Pressure <1 bar: orange warning light. Disable the security management for trunk, pressure drop and customer ARU
	X		Secondary supply of the control box	The 6 bar-calibrated regulator, the 6/4 reducer and the Ø4 coupling are packed in a bag inside the control box
Air from parking brake	X		Air from parking brake	
Exhaust		X	Exhaust	Put a tube L=100mm min. (no muffler)
Emergency stop*		X	Pneumatic emergency stop	
Declutching		X	Declutching actuator (or High speed)	With pneumatic declutching
Footvalve		X	Footvalve opening	
Power take off PTO or Authorisation		X	Power take off or Authorisation	Power take off: leave the plug in place and don't connect any tube in case of electrical control Authorisation: hydraulic control
ARU Emergency stop input	X		Detection of emergency stop requests	ARU are connected in series in a positive safety loop
Trunk	X		Detection of back trunk openings	No air=trunk opened
MS*		X	Timed Master switch	When using the MS pneumatic output
Supply MS*	X		Master switch air supply	When using the MS pneumatic output


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 21 / 49



ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° / °) Temperature: °C
	This document is available at www.alma-alma.fr	Page 22 / 49

Electrical wiring RCT4 remote control receiver

TERMINAL ASSIGNMENT OF THE RCT4 RECEIVER



EQUIPMENT CONNECTED TO THE RCT4 RECEIVER								RCT4 RECEIVER TERMINAL BLOCK				
Option	Equipment	Cable for information)				Function	Colour or No.	Block	Terminal	Function		Observation
		No.	CG*	Alma	Type							
	MICROCOMPT+ Commands	C5			12G1	24VDC	1	BN1	1	24VDC	MICROCOMPT+ POWER SUPPLY	
						0V	2		2	0V		
						IN1 (A)	4	J4	5		AUTHORISATION	
						HS	3		5		HIGH SPEED	
						Author.	4		4		AUTHORISATION	
						Interm. stop	5		3		INTERMEDIATE STOP	
						Measur. end	6		2		MEASURING END	
	CONTROL BOX Commands	C7		●	12G1	Fuse	1	BN1	1		MICROCOMPT+ POWER SUPPLY	
							2	BN1	2			
						EV AU	3	J2	5		SAFETY REQUEST	Emergency stop
						EV Author.	4	J4	4		AUTHORISATION	
						Relay HS	5	J1	7		HIGH SPEED	
						EV PTO	6	J1	5		POWER TAKE OFF	
						Relay MS	7	J2	3		MOTOR STOP	
						EV DC	8	J1	1		DECLUTCHING	or High speed
						EV FV	9		3		FOOTVALVE	
						24VDC	10	J3	1	24VDC	SUPPLY RC CARD AND CRADLE	
						0V	11		2	0V		
									V/J			

*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN H LPG-TRONIC

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

This document is available at www.alma-alma.fr

Page 23 / 49

5.4. ELECTRICAL WIRING WITH CONTROL BOX AND RC LYNX REMOTE CONTROL



ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° / °) Temperature: °C
	This document is available at www.alma-alma.fr	Page 24 / 49

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° / °") Temperature: °C
	This document is available at www.alma-alma.fr	Page 25 / 49

EQUIPMENTS CONNECTED TO THE MICROCOMPT+								INTERFACE POWER SUPPLY BOARD			
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function		Observation
		No.	CG*	Alma	Type						
	CONTROL BOX Commands	C5		●	12G1	24VDC	1	25	24VDC	POWER SUPPLY 24VDC	Ferrite on the supply wire (make a loop)
						0V	2	26	0V		
						Security	3	72	24VDC	SECURITY	
						Author.	4	75	24VDC	AUTHOR.	
						HS	5	73	24VDC	HS	
						PTO	6	61	24VDC	PTO	
						Stop	7	62	24VDC	MS	
						DC	8	76	24VDC	DC	
						FV	9	64	24VDC	FV	
	Pt1000 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100	Connect the shielding
						-	Bc	34	-		
						-	Vt	35	-		
				●		-	-	71	0V		Connect 71to 80
						-	-	80	0V		Connect 71to 80

*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY


THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H LPG-TRONIC


This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C




Electrical wiring control box RC LYNX version

Wiring diagram of the control box RC LYNX version:



Configuration of switches:



Linear switching element for
relays NC or NO contact

Three-position switch for common contact:

- 1→24VDC
2→GND (0V)
3→CS (Free contact)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H

LPG-TRONIC

This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

Page 29 / 49

TERMINAL ASSIGNMENT OF THE CONTROL BOX RC LYNX VERSION



EQUIPMENT CONNECTED TO THE CONTROL BOX								CONTROL BOX TERMINAL BLOCKS				
Option	Equipement	Cable for information)				Function	Colour or No.	Block	Terminal	Function		Observation
		N°	CG*	Alma	Type							
	MICROCOMPT+ Serial links	C6			12x0.34 sh	Tx	Vt	BN1	1	Rx	PRINTER	RS485 serial link Embedded computing (EC) Remote control (RC)
						Rx	Jn		2	Tx		
						0V	Nr		3	0V		
						RS485 -	Rs		4	RS485	EC + RC	
						RS485 +	Bc		5	RS485	EC + RC	
						Recop +	Rg		6	Recop +	RECOPIE	
						Recop -	Gr		7	Recop -	RECOPIE	
						Measur. end	Vi		8		MEASURING END	
						PTO	Mr		9		PTO CONTROL	
						Tx	Bl		10	RS232	EC + RC	RS232 serial link Embedded computing (EC) Remote control (RC)
						Rx	Rg/Bl		11			
	PRINTER	C1		●	2x1	Rx	Vt	BN2	1	Rx	PRINTER	
						Tx	Jn		2	Tx		
						0V	Mr		3	0V		
						24VDC	Bc		4	24VDC		
	POWER SUPPLY					24VDC		BN3 - Bornier client	1	24VDC	POWER SUPPLY	24VDC truck battery (after battery switch and protected by a fuse)
						0V			2	0V	POWER SUPPLY	
	POWER SUPPLY REMOTE CONTROL					24VDC			3	24VDC	POWER SUPPLY RC	
						0V			4	0V	POWER SUPPLY RC	
	RC LYNX BELL								5	-	-	
	MOTOR STOP								6	24VDC/0V/CS	MOTOR STOP	Relay (Configuration 24V, 0V or Free contact)
									7	CS		Only used with configuration Free contact
	PTO								8	24VDC/0V/CS	PTO	Relay (Configuration 24V, 0V or Free contact)
									9	CS		Only used with configuration Free contact
	HIGH SPEED								10	24VDC/0V/CS	HIGH SPEED	Relay (Configuration 24V, 0V or Free contact)
									11	CS		Only used with configuration Free contact
	PTO CONTROL								12	-	-	
	TRUCK TRUNK								13	24VDC/0V/CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact)
									14	CS		Only used with configuration Free contact
	MICROCOMPT+ Commands	C5			12G1	24MC	1	BN4	1	24VDC	MICROCOMPT+ POWER SUPPLY	Fuse
						0MC	2		2	0V		
						Security	3		3	RELAY	SECURITY	Safety request
						Author.	4		4	EV 3/2NC	AUTHOR.	Authorisation
						HS	5		5	RELAY	HS	High speed
						PTO	6		6	EV 3/2NC	PTO	Power take off
						Stop	7		7	RELAY	MS	Motor Stop
						DC	8		8	EV 3/2NC	DC	Decutching (or High Speed)
						FV	9		9	EV 3/2NC	FV	Footvalve
											V/J	

*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN H LPG-TRONIC

This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

5.5. ELECTRICAL WIRING WITH CONTROL BOX AND ASKW REMOTE CONTROL




ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° / °) Temperature: °C
	This document is available at www.alma-alma.fr	Page 32 / 49


TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

**Refer to the Cable Glands Installation Instruction*

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION





Document available on website alma-alma.fr

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H LPG-TRONIC


This document is available at www.alma-alma.fr

Units of measure:
 Length: mm
 Angle: degree (° ' ")
 Temperature: °C

Page 35 / 49

Electrical wiring control box ASKW version

Wiring diagram of the control box ASKW version:



Configuration of switches:

Linear switching element for relays NC or NO contact	Three-position switch for common contact: 1→24VDC 2→GND (0V) 3→CS (Free contact)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° '' ''') Temperature: °C
	This document is available at www.alma-alma.fr	Page 36 / 49

TERMINAL ASSIGNMENT OF THE CONTROL BOX ASKW VERSION



EQUIPMENT CONNECTED TO THE CONTROL BOX								CONTROL BOX TERMINAL BLOCKS						
Option	Equipement	Cable for information)				Function	Colour or No.	Block	Terminal	Function	Observation			
		N°	CG*	Alma	Type									
	MICROCOMPT+ Serial links	C6			12x0.34 sh	Tx	Vt	BN1	1	Rx	PRINTER	RS485 serial link Embedded computing (EC) Remote control (RC)		
						Rx	Jn		2	Tx				
						0V	Nr		3	0V				
						RS485 -	Rs		4	RS485	EC + RC		RS232 serial link Embedded computing (EC) Remote control (RC)	
						RS485 +	Bc		5					
						Tx	Bl		10	RS232	EC + RC			
						Rx	Rg/Bl		11					
	PRINTER	C1		●	2x1	Rx	Vt	BN2	1	Rx	PRINTER			
						Tx	Jn		2	Tx				
						0V	Mr		3	0V				
						24VDC	Bc		4	24VDC				
	POWER SUPPLY					24VDC		BN3 - Bornier client	1	24VDC	POWER SUPPLY	24VDC truck battery (after battery switch and protected by a fuse)		
					0V		2		0V					
	POWER SUPPLY REMOTE CONTROL					24VDC			3	24VDC	POWER SUPPLY RC			
	RC LYNX BELL					0V			4	0V				
	MOTOR STOP								5	-	-			
									6	24VDC/0V/CS	MOTOR STOP	Relay (Configuration 24V, 0V or Free contact)		
									7	CS		Only used with configuration Free contact		
	PTO								8	24VDC/0V/CS	PTO	Relay (Configuration 24V, 0V or Free contact)		
									9	CS		Only used with configuration Free contact		
	HIGH SPEED								10	24VDC/0V/CS	HIGH SPEED	Relay (Configuration 24V, 0V or Free contact)		
									11	CS		Only used with configuration Free contact		
	PTO CONTROL								12	-	-			
	TRUCK TRUNK								13	24VDC/0V/CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact)		
									14	CS	TRUCK TRUNK	Relay Only used with configuration Free contact		
	RECEIVER ASKW (PLC)	C7		●	12G1	24VDC	10	BN3	3	24VDC	POWER SUPPLY RC	Fuse		
						0V	11		4	0V				
						24VDC	1	BN4	1	24VDC	MICROCOMPT+ POWER SUPPLY			
						0V	2		2	0V				
						Author.	4		4	EV 3/2NC	AUTHOR.		Authorisation	
						HS	5		5	RELAY	HS		High speed	
						PTO	6		6	EV 3/2NC	PTO		Power take off	
						Stop	7		7	RELAY	MS		Motor Stop	
						DC	8		8	EV 3/2NC	DC		Declutching (or High Speed)	
						FV	9		9	EV 3/2NC	FV		Footvalve	
						Security	3		BN5	3	RELAY		SECURITY	Safety request
							V/J							

*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY


THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H LPG-TRONIC

This document is available at www.alma-alma.fr


Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

TERMINAL ASSIGNMENT OF THE ASKW RECEIVER (PLC)												
												
EQUIPMENT CONNECTED TO THE ASKW							TERMINAL BLOCK OF THE PLC FOR ASKW					
Option	Equipement	Cable (for information)				Function	Colour or No.	Block	Terminal	Function	Observation	
		N°	CG*	Alma	Type							
	MICROCOMPT+ Commands	C5			12G1	24VDC	1	C7	1	24VDC	Connect to C7	
						0V	2	C7	2	0V	Connect to C7	
						HS	3		I2	HS	High speed	
						Author.	4		I1	AUTHOR.	Authorisation	
						Interm. Stop	5	Q1	1	INTERMEDIATE STOP	Intermediate stop	
						Measur. End	6	Q2	2	MEASURING END	Measuring end	
	CONTROL BOX Commands	C7			12G1	EV Emergency	3	MAQ4	2	SAFETY REQUESTT	Emergency stop	
						EV Author.	4		I1	AUTHOR.	Authorisation	
						Relay HS	5	MAQ1	2	HS	High speed	
						EV PTO	6	MAQ2	2	PTO	Powertake off	
						Relay MS	7	Q3	2	MS	Motor Stop	
						EV DC	8	MAQ3	2	DC	Declutching	
						EV FV	9		I6	FV	Footvalve	
						24VDC	10		L1	24VDC	BOARD 24V-SUPPLY	
								Q3	1			
								Q4	1			
								MAQ1	1			
								MAQ2	1			
								MAQ3	1			
								MAQ4	1			
						0V	11	MA	L1	0V		
								Q1	1			
								Q2	1			
								MA	N			
						Parking brake		MA	I2	24VDC	Parking brake	Present: +24VDC Absent: No authorisation
									I4			

*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	
	This document is available at www.alma-alma.fr	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
		Page 39 / 49

TERMINAL ASSIGNMENT OF THE ASKW RECEIVER (REMOTE CONTROL)



EQUIPMENT CONNECTED TO THE ASKW							ASKW REMOTE CONTROL CABLE		
Option	Equipement	Cable (for information)				Terminal	Block	Cable	Observation
		N°	CG*	Alma	Type				
	ASKW PLC					I3		Vt/Nr	CALL/OPTION
						I4		Bl	DECLUTCHING/STOP
						Refer to Observation		Bc	START If pulse PTO: MAQ1: 2 If continuous PTO: I5
						I6		Nr/Bc	INTERNAL VALVE
						I7		Vt	ACTIVATION OF CONTROL - RELAY
						I8		Rg/Nr	HIGH SPEED Program in pulse mode
						2	Q4	Rg	24VDC Protected 10A
						I1	MA	Or	ON/OFF
						I3			
	MICROCOMPT+	C5		•			2	Nr	GROUND 0V
	CONTROL BOX	C7		•			2		

*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H
LPG-TRONIC

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

This document is available at www.alma-alma.fr

Page 40 / 49

Diagram illustrating the hydraulic system components and their functions:


- Alimentation MS* / *MS air supply** (8 bar max)
- Echappement / *Exhaust*
- Entrée signal ARU / *Emergency stop* (8 bar max)
- Entrée coffre camion / *Trunk* (8 bar max)
- Frein parc / *parking break* (8 bar max)
- Alimentation air / *air supply* (8 bar max)
- Sortie MS* (Master Switch)
- Sortie ARU* (Arrêt d'urgence / *Emergency stop*)
- Sortie DB (Débrayage) / *Declutching* ou GV (Grande Vitesse) pour camion citerne / *High speed*
- Voyant pneumatique vert (signale la présence du frein parc)
- Sortie CF (Clapet de Fond) / *foot valve*
- Sortie PTO (Prise de Mouvement) ou autorisation (commande hydraulique) / *Autori./PTO*
- Régulateur de pression taré à 6 bar (livré avec réducteur et raccord Ø4)

Label	Input	Output	Function	Observation
Air supply	X		Main supply of the control box + detector for pressure drop	Pressure >1 bar: green warning light Pressure <1 bar: orange warning light. Disable the security management for trunk, pressure drop and customer ARU
	X		Secondary supply of the control box	The 6 bar-calibrated regulator, the 6/4 reducer and the Ø4 coupling are packed in a bag inside the control box
Air from parking brake	X		Air from parking brake	
Exhaust		X	Exhaust	Put a tube L=100mm min. (no muffler)
Emergency stop*		X	Pneumatic emergency stop	
Declutching		X	Declutching actuator (or High speed)	With pneumatic declutching
Footvalve		X	Footvalve opening	
Power take off PTO or Authorisation		X	Power take off or Authorisation	Power take off: leave the plug in place and don't connect any tube in case of electrical control Authorisation: hydraulic control
ARU Emergency stop input	X		Detection of emergency stop requests	ARU are connected in series in a positive safety loop
Trunk	X		Detection of back trunk openings	No air=trunk opened
MS*		X	Timed Master switch	When using the MS pneumatic output
Supply MS*	X		Master switch air supply	When using the MS pneumatic output

*Unused ports must be plugged.


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 41 / 49

6. METERING LINE GPL-BALC



6.1. INSTALLATION AND SEALING RECOMMENDATIONS ADRIANE TURBINE METER

- The identification plate and the led of the pulse emitter(s) shall be visible and accessible.
- The turbine must be installed with respect to the flow direction.
- Put sealing rings each other sides between the turbine and the backflanges.
- Leave an open space all around the turbine in order to ease maintenance.
- Install a 400 μ filter (mini) on the pipe upstream from the turbine meter.
- After installation or during the commissioning period, if the new or modified pipes have not been perfectly cleaned or pickled and passivated, the turbine should be protected by a honeycomb sieve – max. 1mm mesh. It must be placed between two flanges upstream from the turbine.
- Dimensions: A > 100mm.



- Refer to the certificate written on the identification plate of the measuring system to suit the sealing requirements
- No loose lead wire on the sealing devices



For accuracy class 0.5 and 1.0 measuring systems, the pipes and equipment upstream or downstream the turbine meter must have the same nominal diameter as the meter on a length at least equal to 10 times this diameter upstream and 5 times this diameter downstream.

These lengths can be straight or bent.

It is mandatory that no flowrate adjustment device (e.g. a variable-opening valve) is located upstream at a distance less than 10 times the nominal diameter of the meter:

Provision contained in EU Type Examination or Evaluation Certificate.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN H LPG-TRONIC

This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

Page 43 / 49

7. PRINTER

Technical data:


- Power supply : 24Vdc $\pm 10\%$
- Current consumption (at 24V) :
 - Mean : approx. 600mA
 - Peak : approx. 5.5A
 - Standby : approx. 100mA
- Temperature : $+5^{\circ}\text{C}$ to $+40^{\circ}\text{C}$
- Mass: 1.6 kg

Printer Link Cable

TYPE	CABLE	COLOUR WIRES	FUNCTION
	Cable 2x0.9mm ² ϕ ext. 5	Black (BK) or White sheathed (WH) White (WH) or Red sheathed (RD) Braid	24V 0v Shielding
	Shielded cable* 4x0.34mm ² ϕ ext. 5.4 L=10m / Code: 3370 L=25m / Code: 3436	White (WH) Brown (BN) Green (GN) Yellow (YE) Braid	Rx printer Tx printer 0v Not used Shielding
	Shielded cable* 4x0.75mm ² ϕ ext. 8 L=5m / Code: 4339 L=10m / Code: 4578	White (WH) Brown (BN) Green (GN) Yellow (YE) Braid	24V 0v Tx printer Rx printer Shielding

* ADR-RTMD - NF R13-413 cable

-
- Technical drawings of the 3D printer showing dimensions A, B, C, and D. Dimension A is the height of the printer. Dimension B is the width of the printer. Dimension C is the length of the printer with the filament spool holder. Dimension D is the length of the printer without the filament spool holder.



DO NOT EXPOSE THE PRINTER TO ANY HEAT-SOURCE.
PROTECT IT FROM VIBRATIONS AND WATER PROJECTIONS.


THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

Page 45 / 49


8. CONVERTER 24VDC/24VDC 2.1A 50W



Document available on website alma-alma.fr

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° / °") Temperature: °C
	This document is available at www.alma-alma.fr	Page 46 / 49

9.1. INSTALLATION RECOMMENDATIONS TEMPERATURE PROBE



REFER TO INSTRUCTION MANUAL
(DELIVERED WITH THE EQUIPMENT AND AVAILABLE ON ALMA WEBSITE)

INSTALLATION OF THE TEMPERATURE SENSOR
ON THE ALMA TURBINE METER:



ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN H LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 48 / 49

159

100

Seals

Security screw

Seal cups

ALMA
www.alma-alma.fr
4A Boulevard de la Gare Portes
P-94470 BOISSY SAINT LEGER

ENSEMBLE DE MESURAGE
MEASURING SYSTEM

Modèle
Model

Type

N° de série
Serial number

Numéro de certificat
Certificate number

Année de fabrication
Year of manufacturing

Classe d'environnement mécanique
Mechanical environment class

Classe d'environnement électromagnétique
Electromagnetic environment class

CE

Classe d'exactitude
Accuracy class

Qté mesurée minimale
Minimum measured quantity

Qté collecteur
Manifold quantity

Température environnement
Environment temperature

Min. Max. °C

Débit
Flow rate

Min. Max.

Pression
Pressure

Min. Max. bar

Liquides mesurés
Measured liquids

Marques
Marks

M5

(Fixed to the frame)

145

86



The security screws of the cups (provided by ALMA) must be screwed in the tap of the frame (do not use removable nuts).