

INSTALLATION GUIDE

DI 005 EN L

LPG-TRONIC

Described in EC-type examination certificate N°: LNE-13621

L	2020/10/12	Corrections on the electrical wiring of the LYNX version	DSM	MV
K	2019/12/10	Connectivity [PJA129], Drawings update	DSM	MV
J	2019/02/26	Configuration of the RCT4 switches, New FORM DOC, Drawings update	DSM/CHR	SR
I	2018/06/11	Functional changes for ASKW	CHR	FDS
Issue	Date	Nature of modifications	Written by	Approved by

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 1 / 54

CONTENTS

1. GENERAL RECOMMENDATIONS	4
1.1. MECANICAL RECOMMENDATIONS	4
1.2. ELECTRICAL RECOMMENDATIONS	5
1.3. PNEUMATIC RECOMMENDATIONS	7
2. GENERAL PRESENTATION	8
2.1. USE ACCORDING TO MID CERTIFICATE	8
2.2. SPECIAL CONDITIONS FOR INSTALLATION IN ANY CASES	8
3. PART LIST	9
4. INSTALLATION AND SEALING DRAWING OF THE LPG-TRONIC	11
5. CALCULATOR-INDICATOR MICROCOMPT+	12
5.1. INSTALLATION RECOMMENDATIONS CALCULATOR-INDICATOR MICROCOMPT+	13
5.2. ELECTRICAL WIRING CALCULATOR-INDICATOR MICROCOMPT+: BASIC VERSION	14
Terminal assignment of the MICROCOMPT+ power supply board basic version	15
Connection of the network board – Ethernet, RS232/485, CANBus	16
Wiring diagram of the 24VDC/24VDC converter for printer	17
5.3. GSM/GPS MODULE EQUIPPED – 2-ANTENNA BOX	18
Mounting and wiring of the GSM and GPS antennas	19
Mounting of the GSM/GPS cables into the cable glands	20
Wiring of the 2-antenna box to the MICROCOMPT+	20
5.4. ELECTRICAL WIRING WITH CONTROL BOX AND RCT4 REMOTE CONTROL	21
Terminal assignment of the MICROCOMPT+ power supply board RCT4 version	22
Control box LPG-TRONIC	23
Electrical wiring control box RCT4 version	25
Pneumatic wiring control box RCT4 version	27
Remote control RCT4	28
Electrical wiring RCT4 remote control receiver	29
5.5. ELECTRICAL WIRING WITH CONTROL BOX AND RC LYNX REMOTE CONTROL	30
Terminal assignment of the MICROCOMPT+ power supply board RC LYNX version	31
Control box LPG-TRONIC	32
Electrical wiring control box RC LYNX version	34
Pneumatic wiring control box RC LYNX version	36
5.6. ELECTRICAL WIRING WITH CONTROL BOX AND ASKW REMOTE CONTROL	37
Terminal assignment of the MICROCOMPT+ power supply board ASKW version	38
Control box LPG-TRONIC	39
Electrical wiring control box ASKW version	41
Electrical wiring ASKW remote control receiver/PLC	43
Pneumatic wiring control box ASKW version	46
6. METERING LINE GPL-BALC	47
6.1. INSTALLATION AND SEALING RECOMMENDATIONS ADRIANE TURBINE METER	48
7. PRINTER	49
7.1. INSTALLATION RECOMMENDATIONS PRINTER	50

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 2 / 54

8. CONVERTER 24VDC/24VDC 2.1A 50W	51
9. TEMPERATURE PROBE PT100 – CT1001	52
9.1. INSTALLATION RECOMMENDATIONS TEMPERATURE PROBE.....	53
10. KIT FOR MEASURING SYSTEM IDENTIFICATION PLATE.....	54

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 3 / 54

1. GENERAL RECOMMENDATIONS

IN ORDER TO AVOID ALL THE PROBLEMS CONCERNING THE INSTALLATION, THE OPERATION AND THE MAINTENANCE OF THE EQUIPMENTS, BEING ABLE TO CREATE INOPPORTUNE FAILURE, PLEASE RESPECT THE FOLLOWING RECOMMENDATIONS.

BEFORE ANY WORK, MAKE SURE THAT THE EQUIPMENTS ARE NOT POWERED.


1.1. MECANICAL RECOMMENDATIONS

- ⇒ Respect the recommendations of the instruction manual specifying the installation, operation and maintenance conditions of the ATEX equipment (instruction manual supplied with the equipment).
- ⇒ Take care to place the equipment in order to facilitate their installation, operation and maintenance by the technicians (working ergonomics).
- ⇒ Take care to position properly the equipment; the display must be readable without any difficulty.
- ⇒ Apply a tightening torque suitable with size and material of the fixation element except particular specifications mentioned on the presentation drawing or in the installation guides.
- ⇒ Mechanically protect the cables with the corrugated conduit if the cables are not ADR (corrugated conduit adapted to vehicles used for 'carriage of dangerous goods of road' - hydrocarbons, LPG ... - and meet the requirements of French standard NF R13-903. Refer to the regulations in force).
- ⇒ Ensure there are a good mechanical strength and a good sealing between cable glands and cables, and between cable glands and corrugated conduit.
- ⇒ Respect cables and corrugated conduit radii of curvature.
- ⇒ Leave enough flexibility to wires in order to avoid any risk of stripping.
- ⇒ Allow the drainage of the water in the lower loop (siphon) of the corrugated conduit (not water retention inside the corrugated conduit).
- ⇒  See § INSTALLATION AND SEALING RECOMMENDATIONS ADRIANE TURBINE METER.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 4 / 54

1.2. ELECTRICAL RECOMMENDATIONS

- ⇒ According to the ATEX directive or any other regulations in force in the country of destination, the safety protection level of the equipment must agree with the installation area (potentially explosive atmospheres).
- ⇒ Respect the recommendations of the instruction manual specifying the installation, operation and maintenance conditions of the ATEX equipment (instruction manual supplied with the equipment).
- ⇒ Connect the supply of the equipment downstream cut-out, on the power supply reserved to the measured distribution.
- ⇒ Put a delayed protection of 5A upstream the 24VDC supply to protect equipment in case of reverse polarity or overcurrent.
- ⇒ Use ADR specific cable, if it is not the case, use at minimum a cable resisting to hydrocarbons. Mechanically protect this cable with a corrugated conduit (corrugated conduit adapted to vehicles used for 'carriage of dangerous goods by road' - hydrocarbons, LPG ... - and meet the requirements of French standard NF R13-903. Refer to the regulations in force).
- ⇒ Take care not to damage the terminals of the different electronic boards while wiring.
 - Screw terminals: do not damage the screw heads of the terminals.
 - Use insulated lugs and insulated wire ferrules adapted to the section of wires.
 - Spring terminals: do not block the springs (if a spring is blocked, the electronic board must be replaced).
 - Use flat screwdriver 0.4x2.5 (see fig.1).
 - Insert the screwdriver slightly tilted, then push it perpendicularly to the terminal.
 - Do not exceed the upright position when the screwdriver is down in order not to block the spring.
 - Insert or remove the wire and remove the screwdriver.
- ⇒ Pass the power supply cores (24VDC truck) through the ferrites by carrying out a loop (ALMA supply).
- ⇒ Do not use wires of section higher than 1.5mm².
- ⇒ Do not insert more than two wires in a terminal, if necessary use an insulated twin wire ferrule (unless otherwise indicated).
- ⇒ Strictly respect the polarities of the input/output when wiring, in accordance with serigraphy on the cards and/or with the installation guide indications.
- ⇒ Whenever possible, perform a wired test, after wiring and before powering.
- ⇒ Whenever possible, respect the locations of the cables specified in the installation guide.
- ⇒ Equipment must be connected to the frame ground (external ground connection).
- ⇒ Whenever possible, use shielded cables with a 360° connection through the metal cable glands (see the documentation delivered with the equipment).
Otherwise, connect the shields to devices inside the equipment (ground terminal, earth bar, earth boss...).
- ⇒ Whenever possible, label the cables and cores according to the installation guide to facilitate the later maintenance operations.



ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 5 / 54

- ⇒ Respect a homogeneous wire color code.
- ⇒ Printer TMU295: before positioning the printer on its support, check that configuration switches of the data link protocol, located under the printer, are well positioned: No3 on 'ON' and the 7 others on 'OFF'.
- ⇒ Current of the electrical devices:

Electrical devices	Supply voltage	Minimum current	Maximum current
MICROCOMPT+	24VDC +/-10%	0.7 A	1.5 A
PRINTER	24VDC +/-10%	0.1 A	5.5 A (switch-on)

- ⇒ Color code according to DIN 47100.
- ⇒ Code for designation of colours according to IEC 60757 (except FR codes):

FR				EN	IT	ES	DE
Couleurs	Codes		Standard codes CEI 60757	Colours	Colori	Colores	Farbe
Blanc	Bc		WH	White	Bianco	Blanco	Weiß
Marron	Mr		BN	Brown	Marrone	Marrón	Braun
Vert	Vt		GN	Green	Verde	Verde	Grün
Jaune	Jn		YE	Yellow	Giallo	Amarillo	Gelb
Gris	Gr		GY	Grey	Grigio	Gris	Grau
Rose	Rs		PK	Pink	Rosa	Rosa	Lila
Bleu	Bl		BU	Blue	Blu	Azul	Blau
Rouge	Rg		RD	Red	Rosso	Rojo	Rot
Noir	Nr		BK	Black	Nero	Negro	Schwarz
Violet	Vi		VL	Violet	Viola	Violeta	Violett
Orange	Or		OG	Orange	Arancio	Naranja	Orange
Vert/Jaune	V/J		GNYE	Green/Yellow	Verde/Giallo	Verde/Amarillo	Grün/Gelb

1.3. PNEUMATIC RECOMMENDATIONS

- ⇒ Air must be filtered – from 40 to 20µm. Specific recommendations may be added in the installation guides or on the presentation drawings.
- ⇒ The air lubrication must be permanent and correct to avoid any damage on the pneumatic components.
- ⇒ The air supply pressure to the inlet of the equipment must be at least 6 bar and max 8 bar. Specific recommendations may be added in the installation guides or on the presentation drawings.
- ⇒ The pneumatic supply pipes (6/4) must be cut straight (no slanting cut) and should not be crushed after cutting to prevent leakage on fittings.
- ⇒ Respect the radii of curvature of the pneumatic pipes indicated by the manufacturer.
- ⇒ Use colored pneumatic pipes to ease maintenance operation.
- ⇒ In no case the exhaust holes of the pneumatic organs should be plugged, obstructed, unless if that is clearly specified in the installation guides or on presentation drawings.
- ⇒ The use of muffler is not allowed under any circumstances (fouling, frost...). Put a pneumatic pipe of sufficient length, pointed downwards, so that its end is placed in a protected area (L = 100 mm min.).
- ⇒ Pressure unit conversion:

PRESSURE UNIT CONVERSION				
Unités	Bar	PSI	Pascal	kg/cm ²
1 Bar =	1	14,5	100 000 (1x10 ⁵)	1,0197
1 PSI =	0.069	1	6894,5	0,07031
1 Pascal =	1x10 ⁻⁵	14,5x10 ⁻⁵	1	1,0197x10 ⁻⁵
1 kg/cm ² =	0,98	14,22	98066,5	1

PSI = Pound per Square Inch (livre par pouce carré)

1 bar = 100 kPa = 0.1 MPa (1 MPa = 10 bar)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 7 / 54

2. GENERAL PRESENTATION

2.1. USE ACCORDING TO MID CERTIFICATE

The LPG TRONIC measuring system is covered by the EU type examination certificate N° LNE-13621. Refer to this certificate for any precision about its installation.


For the sealing plan, see Annex to EU type examination certificate N° LNE-13621.

2.2. SPECIAL CONDITIONS FOR INSTALLATION IN ANY CASES

- ⇒ Safety valves may be incorporated in the ALMA LPG-TRONIC measuring system. If they are located downstream of the turbine meter, they must open to the atmosphere or be connected to the receiving tank. In no case may safety valves located upstream of the turbine meter be connected to the valves located downstream by pipes that bypass the turbine meter.
- ⇒ To prevent any hydraulic connection of bottle under pressure, the purge below the gas separator must finish on a smooth stiff pipe, without threading nor join, and which is not take down.


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 8 / 54

3. PART LIST

EQUIPMENTS INCLUDED IN THE MEASURING SYSTEM DELIVERED BY ALMA				
Item	Equipment	Designation	Qty	Option*
1		CALCULATOR INDICATOR MICROCOMPT+ LPG TRONIC WITH Bluetooth CONNECTION	1	
		Wi-Fi CONNECTION (As an alternative to Bluetooth)		•
		RFID SUPERVISOR KEY		
2		GPL TRONIC CONTROL BOX (Provided with RS232-serial link and power supply for printer)	1	•
3	3.a 	METERING LINE GPL-BALC (Gas separator – ADRIANE turbine meter DN50-30 – differential valve)	1	
	3.b 	ADRIANE TURBINE METER DN50-30 BALC		

Non-contractual pictures


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 9 / 54

EQUIPMENTS INCLUDED IN THE MEASURING SYSTEM DELIVERED BY ALMA				
Item	Equipment	Designation	Qty	Option*
4	4a 	PRINTER TMU-295 (Printer – printer holder – cable 5 or 10m)	1	
	4b 	CONVERTER 24VDC/24VDC 2.1A 50W Provided if there is no control box (With RS232 serial link wire and 24VDC power supply for printer)	1	●
5		REMOTE CONTROL RCT4	1	●
6		Pt100 TEMPERATURE SENSOR – CT1001-Pe (Supplied with thermowell)	1	
7		2-ANTENNA BOX GSM AND GPS	1	●
8		KIT FOR MEASURING SYSTEM IDENTIFICATION PLATE (Plate and sealing device)	1	●
Option*: equipment sold as an option by ALMA, it must be installed on the measuring system if required by the certificate.				

Non-contractual pictures

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 10 / 54

4. INSTALLATION AND SEALING DRAWING OF THE LPG-TRONIC



Legend:

- Clf: Foot valve
 Pg: Line purge in the atmosphere (can be collected between them)
 Va: Control valve allowing liquid to flow.
 R1: Two-way cock for deliveries with meter and for draining or filling tank without meter. This device is optional and may be replaced by a direct connection.
 F: Filter
 Vm: Operation valve (optional).
 B: Adjustable bypass connected to tank
 Mo: Manometer (optional)
 P: Pump
 R2: Three-way cock (optional) for direct delivery without meter.
 Cla: Non-return valve fitted to block comprising filter and gas separator
 F1: Filter fitted to gas separator
 Sg: Gas separator, connected to gaseous phase of tank. If a safety valve (Vas) is fitted to this device, it must be placed between the tank and the diversion from the pressure control valve (Vamp).
 Vas: Automatic safety valve (optional)
 Th: Thermometer. The thermometer must be located close to the meter, either in the gas separator or at the meter inlet or outlet.
 C: Meter
 TT: Pt100 temperature sensor (optional).
 Vamp: Pressure control valve, regulated to maintain pressure at least 1 bar higher than saturated vapour pressure in the tank
 M: Manometer
 S: Valve of thermal expansion
 Vma: Operation valve
 VSP: Three ways faucet allowing a delivery by two ways of distribution
 FI1: Full hose
 Z: Gaseous phase piping, to be used only for filling vehicle tank or for draining tank when measuring system is verified.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 11 / 54

5. CALCULATOR-INDICATOR MICROCOMPT+




Document available on website alma-alma.fr


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	
	This document is available at www.alma-alma.fr	Units of measure: Length: mm Angle: degree (° '' ''') Temperature: °C
Page 12 / 54		

5.1. INSTALLATION RECOMMENDATIONS CALCULATOR-INDICATOR MICROCOMPT+


- Fasten the box with 4 M6 screws (holder suitable for vibrations and designed to support the MICROCOMPT). On the box: 4 M6 blind holes tapped length=12 over 185x132).
- Leave an open space around the box in order:
 - o To facilitate maintenance operation.
 - o To prevent any pressing on pushbuttons and on the glass.
- The space between the front face of the box and the cabinet door shall be sufficient.
- Dimensions: $A > 100\text{mm}$ and $B > 60\text{mm}$



- SOLUTION 1: straight box if it's a breast height.




Left hand view
Closed box



Left hand view
open box

- SOLUTION 2: 20° angle if it's not at breast height.



Left hand view
Closed box



Left hand view
open box

REFER TO THE INSTRUCTION MANUAL
(DELIVERED WITH THE EQUIPMENT OR AVAILABLE ON ALMA WEBSITE)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN L LPG-TRONIC

This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

Page 13 / 54

5.2. ELECTRICAL WIRING CALCULATOR-INDICATOR MICROCOMPT+: BASIC VERSION




Terminal assignment of the MICROCOMPT+ power supply board basic version

Any mass braids and shielding must be connected to the MICROCOMPT+ ground bar

TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

POWER SUPPLY BOARD



EQUIPMENTS CONNECTED TO THE MICROCOMPT+								POWER SUPPLY BOARD			
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function		Observation
		No.	CG*	Alma	Type						
•	PRINTER	C1	1/2"NPT	●	ADR 4x0.34 sh.	Rx	Bc	1	Tx	PRINTER	Connect the shielding
						Tx	Mr	2	Rx		
						0V	Vt	3	0V		
	EMBEDDED COMPUTING	C6			3x0.34 sh.	Rx	Bc	6	Tx	GPS / GSM / EC	Connect the shielding
						Tx	Mr	7	Rx		
						0V	Vt	8	0V		
	TURBINE TRANSMITTER	C3	1/2"NPT		ADR 4x0.34 sh.	12V	Jn	11	12V	TURBINE INPUT	Connect the shielding
						V1	Mr	12	V1		
						V2	Vt	13	V2		
						0V	Bc	14	0V		
	24VDC-INPUT truck (battery)	C5 bis			2x1	Bat (+)	1	25	24VDC	POWER SUPPLY 24VDC	
						Bat (-)	2	26	0V		
	INTERMEDIATE STOP	C5			7X1	Interm. Stop	5	49	24VDC	INTERM. STOP	Free contact from the vehicle automatic process
	MEASURING END					Measur. end	6	50	24VDC	MEASURING END	Free contact from the vehicle automatic process
	HIGH FLOWRATE					HF	3	74	24VDC	HIGH SPEED	24VDC-output to the vehicle automatic process
	AUTHORISATION CHANNEL 1					Author.	4	75	24VDC	AUTHOR. CHANNEL 1	Connect the 24VDC- output in series with the vehicle automatic process
	AUTHORISATION CHANNEL 2					Author.	7	63	24VDC	AUTHOR. CHANNEL 2	Connect the 24VDC- output in series with the vehicle automatic process
	Pt100 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100	Connect the shielding
						-	Bc	34	-		
						-	Vt	35	-		


*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 15 / 54

Connection of the network board – Ethernet, RS232/485, CANBus

Connection to the Ethernet network:

- With the RJ45 connector according to the EIA/TIA-568 standard
- Or with the screw-terminal: see details in the table below.



NETWORK BOARD

NETWORK CONNECTION TYPE

Option	Connection	Cable (for information)				Function	Coulor or No.	NETWORK BOARD		
		No.	CG*	Alma	Type			Coulor	Function	Observation
	ETHERNET NETWORK						Vt/Bc	Tx+	Ethernet	Or connection with RJ45 according to EIA/TIA- 568
							Vt	Tx-		
							Or/Bc	Rx+		
							Or	Rx-		
	RS232 or RS485						Tx / A	RS232 or RS485	Depending on the switch configuration See above	
							Rx / B			
							GND			
	CANBus NETWORK						CAN+	CANBus		
							CAN-			
							GND			

*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN L
LPG-TRONIC

This document is available at www.alma-alma.fr


Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

Page 16 / 54

Wiring diagram of the 24VDC/24VDC converter for printer




5.3. GSM/GPS MODULE EQUIPPED – 2-ANTENNA BOX



Document available on website [alma-alma.fr](http://www.alma-alma.fr)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° '' ''') Temperature: °C
	This document is available at www.alma-alma.fr	Page 18 / 54




ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° + ' + ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 19 / 54

Mounting of the GSM/GPS cables into the cable glands

ALMA connects the GSM and GPS antenna to the MICROCOMPT+ (2-antenna board).



At the outlet of the MICROCOMPT+ box, you must pass both cables through cable glands. In case of an ATEX MICROCOMPT+, cable glands must be ATEX.



RECOMMENDED CABLE GLANDS
(FOR INFORMATION ONLY)

Into the MICROCOMPT+, adjust the cable length to easily open and close the cover. Make sure to prevent damage to the cable.

Tighten both cable glands.

Wiring of the 2-antenna box to the MICROCOMPT+

Fasten the box. You must install it in an area free of metallic cover to have a good reception and broadcasting of signal. You can install the box in a horizontal or vertical position.

Put each coaxial cable through the heat shrink sleeve.

Plug the RG58⁽¹⁾ cable from the MICROCOMPT+ with the RG174⁽²⁾ cable from the antenna box and tighten them. Isolate the male/female SMA connectors with the supplied heat shrink sleeve (both antennas in the box are the same, cables don't have to be labelled).

Position and heat up the sleeve on the connectors to prevent corrosion and humidity.



WARNING: The cables of this box can be **neither shortened nor extended**

⁽¹⁾ RG58: Semi-rigid coaxial cable, 5mm diameter

⁽²⁾ RG174: Flexible coaxial cable, 2.7mm diameter

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN L
LPG-TRONIC

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

This document is available at www.alma-alma.fr

Page 20 / 54




Terminal assignment of the MICROCOMPT+ power supply board RCT4 version

Any mass braids and shielding must be connected to the MICROCOMPT+ ground bar

TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

POWER SUPPLY BOARD



EQUIPMENTS CONNECTED TO THE MICROCOMPT+								POWER SUPPLY BOARD			
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function		Observation
		No.	CG*	Alma	Type						
	CONTROL BOX serial links	C6		●	ADR 12x0.34 sh.	Rx	Vt	1	Tx	PRINTER	Serial link RS232 Embedded computing (EC) Remote control (RC)
						Tx	Jn	2	Rx		
						0V	Nr	3	0V		
						Rx	Bl	4	Tx	RS232 EC + RC	
						Tx	Rg/Bl	5	Rx		
						RS485+	Bc	9	RS485+	RS485 EC + RC	Serial link RS485 Embedded computing (EC) Remote control (RC)
						RS485-	Rs	10	RS485-		
						Pulses output +	Rg	22	S	PULSES OUTPUT	
						Pulses output -	Gr	24	0V		
						Mesur. End	Vi	53	24VDC	MEASURING END	
PTO control	Mr	58	PTO	PTO CONTROL							
	TURBINE TRANSMITTER	C3	1/2"NPT		ADR 4x0.34 sh.	12V	Jn	11	12V	TURBINE INPUT	Connect the shielding
						V1	Mr	12	V1		
						V2	Vt	13	V2		
						0V	Bc	14	0V		
	RECEIVER RCT4 Commands	C5		●	12G1	24VDC	1	25	24VDC	POWER SUPPLY 24VDC	High speed Authorisation Intermediate stop Measuring end
						0V	2	26	0V		
						HS	3	74	24VDC	HIGH SPEED	
						Author.	4	75	24VDC	AUTHOR.	
						Interm. stop	5	49	24VDC	INTERM. STOP	
						Measuring end	6	50	24VDC	MEASURING END	
	Pt1000 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100	Connect the shielding
						-	Bc	34	-		
						-	Vt	35	-		

*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN L LPG-TRONIC

This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° '' ''')
Temperature: °C

Page 22 / 54

Control box LPG-TRONIC

Customer cable gland:
- 2 PG13 cable Ø6-12
- 1 PG09 cable Ø4-8

Pneumatic block

Pneumatic indicator (presence air brake park)

M (1 : 2)

Emergency stop from customer

From Trunk

Air supply

From parking brake

3 Sub-D 9pts male

Regulator calibrated at 6 bar and fittings packed in bag

Luminous power button

Vent plug (do not block)

Print cable L=5m power supply and RS232

Technical features

- Box (No ATEX): 250x200x159 material ABS with transparent lid.
- Protection level : IP50
- Temperature: -10° to +60°C
- Mass (except wiring): about 3.2 kg
- Electrical part:
 - Input power 24Vcc (truck).
 - Customer terminal block BN3: 1.5mm² max.
 - Solenoid valves control: 24Vdc ±10% - 1.2W
- Pneumatic part:
 - Pneumatic (4 output 3/2NC).
 - Fluid: 40µm filtered air lubricated or not
 - Operating Pressure: 10 bar max.
 - Flowrate at 6 bar: 500 Nl/min.
 - Pneumatic fittings: for tube Ø6.
 - Unused outputs must be plugged.

DESCRIPTION OF MODIFICATION 686:
Changing the start button label

PRESENTATION DRAWING		DFN045
Control box		
907	PPN045	E 9 / 10
Dev N°	Drawing N°	Folio
		Created on : 05/06/2012
		Modified on : 18/09/2019
		by EG
		ROC verified by
		CHR XS

NOTE: Overall dimensions on next folio

Document available on website [alma-alma.fr](http://www.alma-alma.fr)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN L LPG-TRONIC


This document is available at www.alma-alma.fr

Units of measure:
 Length: mm
 Angle: degree (° '' ''')
 Temperature: °C

Page 23 / 54


Electrical wiring control box RCT4 version

Wiring diagram of the control box RCT4 version:



Configuration of switches:

PTO (Power take off), Motor stop (AR MOT), High speed (GD. VIT.), RC LYNX, Truck trunk (COFFRE), Master Switch (M. SW), SW9 and SW13:

		
Linear switching element for relays NC or NO contact	Three-position switch for common contact of the relay: 1 → 24VDC 2 → GND (0V) 3 → CS (Free contact)	SW9 → DEBR. (Declutching) or GD. VIT. (H. speed) for semi trailer SW13 → 24V for PTO or AUTOR for semi trailer

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° + ' + ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 25 / 54




EQUIPMENT CONNECTED TO THE CONTROL BOX												
Option	Equipement	Cable for information)				Function	Colour or No.	Block	Terminal	Function		Observation
		N°	CG*	Alma	Type							
	MICROCOMPT+ Serial links	C6			12x0.34 sh	Tx	Vt	BN1	1	Rx	PRINTER	RS485 serial link Embedded computing (EC) Remote control (RC) RS232 serial link Embedded computing (EC) Remote control (RC)
Rx						Jn	2		Tx			
0V						Nr	3		0V			
RS485 -						Rs	4		RS485	EC + RC		
RS485 +						Bc	5		RS232	EC + RC		
Tx						Bl	10					
Rx						Rg/Bl	11					
	PRINTER	C1		●	2x1	Rx	Vt	BN2	1	Rx	PRINTER	
Tx						Jn	2		Tx			
0V						Mr	3		0V			
24VDC						Bc	4		24VDC			
	POWER SUPPLY					24VDC		BN3 - Bornier client	1	24VDC	POWER SUPPLY	24VDC truck battery (after battery switch and protected by a fuse)
	RC LYNX BELL					0V			2	0V		
	MOTOR STOP								5	-	-	
									6	24VDC/0V/CS	MOTOR STOP	Relay (Configuration 24V, 0V or Free contact)
									7	CS		Only used with configuration Free contact
	PTO								8	24VDC/0V/CS	PTO	Relay (Configuration 24V, 0V or Free contact)
									9	CS		Only used with configuration Free contact
	HIGH SPEED								10	24VDC/0V/CS	HIGH SPEED	Relay (Configuration 24V, 0V or Free contact)
									11	CS		Only used with configuration Free contact
									12	-	-	
	TRUCK TRUNK								13	CS	TRUCK TRUNK	Only used with configuration Free contact
									14	24VDC/0V/CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact)
	RECEIVER RCT4	C7	●	12G1	24VDC	10	BN3		3	24VDC	SUPPLY CARD AND CRADLE	Power supply for the remote control card and cradle
0V					11	4			0V			
24VDC					1	BN4	1	24VDC	MICROCOMPT + POWER SUPPLY	Fuse		
0V					2		2	0V	AUTHOR.			
Author.					4		4	EV 3/2NC		Authorisation		
HS					5		5	RELAY	HS	High speed		
PTO					6		6	EV 3/2NC	PTO	Power take off		
Stop					7		7	RELAY	MS	Motor Stop		
DC					8		8	EV 3/2NC	DC	Declutching (or High Speed)		
FV					9		9	EV 3/2NC	FV	Footvalve		
Security					3		BN6	5	RELAY	SECURITY	Safety request	
					V/J							

**Refer to the Cable Glands Installation Instructions*

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° / °") Temperature: °C
	This document is available at www.alma-alma.fr	Page 26 / 54


Pneumatic wiring control box RCT4 version



Label	Input	Output	Function	Observation
Air supply	X		Main supply of the control box + detector for pressure drop	Pressure >1 bar: green warning light Pressure <1 bar: orange warning light. Disable the security management for trunk, pressure drop and customer ARU
	X		Secondary supply of the control box	The 6 bar-calibrated regulator, the 6/4 reducer and the Ø4 coupling are packed in a bag inside the control box
Air from parking brake	X		Air from parking brake	
Exhaust		X	Exhaust	Put a tube L=100mm min. (no muffler)
Emergency stop*		X	Pneumatic emergency stop	
Declutching		X	Declutching actuator (or High speed)	With pneumatic declutching
Footvalve		X	Footvalve opening	
Power take off PTO or Authorisation		X	Power take off or Authorisation	Power take off: leave the plug in place and don't connect any tube in case of electrical control Authorisation: hydraulic control
ARU Emergency stop input	X		Detection of emergency stop requests	ARU are connected in series in a positive safety loop
Trunk	X		Detection of back trunk openings	No air=trunk opened
MS*		X	Timed Master switch	When using the MS pneumatic output
Supply MS*	X		Master switch air supply	When using the MS pneumatic output


*Unused ports must be plugged.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 27 / 54



Electrical wiring RCT4 remote control receiver

TERMINAL ASSIGNMENT OF THE RCT4 RECEIVER



EQUIPMENT CONNECTED TO THE RCT4 RECEIVER								RCT4 RECEIVER TERMINAL BLOCK					
Option	Equipment	Cable for information)				Function	Colour or No.	Block	Terminal	Function		Observation	
		No.	CG*	Alma	Type								
	MICROCOMPT+ Commands	C5			12G1	24VDC	1	BN1	1	24VDC	MICROCOMPT+ POWER SUPPLY		
						0V	2		2	0V			
						IN1 (A)	4	J4	5		AUTHORISATION		
						HS	3		5		HIGH SPEED		
						Author.	4		4		AUTHORISATION		
						Interm. stop	5		3		INTERMEDIATE STOP		
						Measur. end	6		2		MEASURING END		
	CONTROL BOX Commands	C7		●	12G1	Fuse	1	BN1	1		MICROCOMPT+ POWER SUPPLY		
							2		2				
						EV AU	3	J2	5		SAFETY REQUEST	Emergency stop	
						EV Author.	4	J4	4		AUTHORISATION		
						Relay HS	5	J1	7		HIGH SPEED		
						EV PTO	6		5		POWER TAKE OFF		
						Relay MS	7	J2	3		MOTOR STOP		
						EV DC	8	J1	1		DECLUTCHING	or High speed	
						EV FV	9		3		FOOTVALVE		
						24VDC	10	J3	1	24VDC	SUPPLY RC CARD AND CRADLE		
						0V	11		2	0V			
											V/J		

*Refer to the Cable Glands Installation Instructions

Configuration of switches:

	Switches position Default configuration 6 → OFF 5 → OFF 4 → ON 3 → OFF 2 → OFF 1 → OFF	Terminal J4: Enable or disable the function with switches 7 → IN4 PTO (ON=pulse 3 seconds) 6 → IN3 Parking brake 5 → IN2 High speed authorization Alma 4 → IN1 Anti-fraud Alma 3 → OUT2 Intermediate stop Alma 2 → OUT1 End of delivery Alma 1 → Ground

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN L LPG-TRONIC

This document is available at www.alma-alma.fr
Units of measure:
Length: mm
Angle: degree (° '' ''')
Temperature: °C

Page 29 / 54

5.5. ELECTRICAL WIRING WITH CONTROL BOX AND RC LYNX REMOTE CONTROL




Terminal assignment of the MICROCOMPT+ power supply board RC LYNX version

Any mass braids and shielding must be connected to the MICROCOMPT+ ground bar

TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

POWER SUPPLY BOARD



EQUIPMENTS CONNECTED TO THE MICROCOMPT+								POWER SUPPLY BOARD				
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function		Observation	
		No.	CG*	Alma	Type							
	CONTROL BOX serial links	C6		●	ADR 12x0.34 sh.	Rx	Vt	1	Tx	PRINTER	Serial link RS232 Embedded computing (EC) Remote control (RC)	
						Tx	Jn	2	Rx			
						0V	Nr	3	0V			
							Bl	4	Tx	RS232 EC + RC		Serial link RS485 (RC Lynx) Embedded computing (EC) Remote control (RC)
							Rg/Bl	5	Rx			
						RS485 +	Bc	9	+	RS485 EC + RC		
						RS485 -	Rs	10	-			
						Pulses output +	Rg	22	S	PULSES OUTPUT		
						Pulses output -	Gr	24	0V			
						Mesur. End	Vi	50	24VDC	MEASURING END PTO CONTROL		
PTO control	Mr	58	PTO									
	TURBINE TRANSMITTER	C3	1/2"NPT		ADR 4x0.34 sh.	12V	Jn	11	12V	TURBINE INPUT	Connect the shielding	
						V1	Mr	12	V1			
						V2	Vt	13	V2			
						0V	Bc	14	0V			
	CONTROL BOX commands	C5		●	12G1	24VDC	1	25	24VDC	POWER SUPPLY 24VDC	Ferrite on the supply wire (make a loop)	
						0V	2	26	0V			
						Security	3	72	24VDC	SECURITY		
						Author.	4	75	24VDC	AUTHOR.		Authorisation
						HS	5	73	24VDC	HS		High speed
						PTO	6	61	24VDC	PTO		Power take off
						Stop	7	62	24VDC	MS		Motor stop
						DC	8	76	24VDC	DC		Declutching (for High speed)
FV	9	64	24VDC	FV	Footvalve							
	Pt100 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100	Connect the shielding	
						-	Bc	34	-			
						-	Vt	35	-			
				●		-	71	0V		Connect 71to 80		
						-	80	0V		Connect 71to 80		

*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN L LPG-TRONIC

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

This document is available at www.alma-alma.fr

Page 31 / 54

Control box LPG-TRONIC

Technical features

- Box (No ATEX): 250x200x159 material ABS with transparent lid.
- Protection level : IP50
- Temperature: -10° to +60°C
- Mass (except wiring): about 3.2 kg
- Electrical part:
 - Input power 24Vcc (truck).
 - Customer terminal block BN3: 1.5mm² max.
 - Solenoid valves control: 24Vdc ±10% - 1.2W
- Pneumatic part:
 - Pneumatic (4 output 3/2NC).
 - Fluid: 40µm filtered air lubricated or not
 - Operating Pressure: 10 bar max.
 - Flowrate at 6 bar: 500 Nl/min.
 - Pneumatic fittings: for tube Ø6.
 - Unused outputs must be plugged.

NOTE: Overall dimensions on next folio

DESCRIPTION OF MODIFICATION 686:
Changing the start button label

PRESENTATION DRAWING		DFN045
Control box		
907	PPN045	E 9 / 10
Dev N°	Drawing N°	Folio
907	PPN045	Rev
Dev N°	Drawing N°	Created on : 05/06/2012
Dev N°	Drawing N°	Modified on : 18/09/2019
Dev N°	Drawing N°	by EG
Dev N°	Drawing N°	ROC verified by
Dev N°	Drawing N°	CHR
Dev N°	Drawing N°	XS

ALMA Service Development
13127 Vitrolles
www.alma-alma.fr
DEV N° : 907 Code : 1073
Drawing N° associated with the related CERT file
Metro :
ATEX:

NOTE: Overall dimensions on next folio

Document available on website [alma-alma.fr](http://www.alma-alma.fr)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN L LPG-TRONIC

This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° '' ''')
Temperature: °C

Page 32 / 54



Document available on website www.alma-alma.fr

TERMINAL ASSIGNMENT OF THE CONTROL BOX RC LYNX VERSION



EQUIPMENT CONNECTED TO THE CONTROL BOX								CONTROL BOX TERMINAL BLOCKS				
Option	Equipement	Cable for information)				Function	Colour or No.	Block	Terminal	Function		Observation
		N°	CG*	Alma	Type							
	MICROCOMPT+ Serial links	C6			12x0.34 sh	Tx	Vt	BN1	1	Rx	PRINTER	RS485 serial link Embedded computing (EC) Remote control (RC)
						Rx	Jn		2	Tx		
						0V	Nr		3	0V		
						RS485 -	Rs		4	RS485		
						RS485 +	Bc		5	RS485		
						Recop +	Rg		6	Recop +	RECOPIE	
						Recop -	Gr		7	Recop -		
						Measur. end	Vi		8		MEASURING END	
						PTO	Mr		9		PTO CONTROL	
						Tx	Bl		10	RS232	EC + RC	RS232 serial link Embedded computing (EC) Remote control (RC)
						Rx	Rg/Bl		11			
	PRINTER	C1		●	2x1	Rx	Vt	BN2	1	Rx	PRINTER	
						Tx	Jn		2	Tx		
						0V	Mr		3	0V		
						24VDC	Bc		4	24VDC		
	POWER SUPPLY					24VDC		BN3 - Bomier client	1	24VDC	POWER SUPPLY	24VDC truck battery (after battery switch and protected by a fuse)
					0V		2		0V			
	POWER SUPPLY REMOTE CONTROL					24VDC			3	24VDC	POWER SUPPLY RC	
	RC LYNX BELL					0V			4	0V		
	MOTOR STOP								6	24VDC/0V/CS	MOTOR STOP	Relay (Configuration 24V, 0V or Free contact)
									7	CS		Only used with configuration Free contact
	PTO								8	24VDC/0V/CS	PTO	Relay (Configuration 24V, 0V or Free contact)
									9	CS		Only used with configuration Free contact
	HIGH SPEED								10	24VDC/0V/CS	HIGH SPEED	Relay (Configuration 24V, 0V or Free contact)
									11	CS		Only used with configuration Free contact
	PTO CONTROL								12	-	-	
	TRUCK TRUNK								13	CS	TRUCK TRUNK	Only used with configuration Free contact
									14	24VDC/0V/CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact)
	MICROCOMPT+ Commands	C5			12G1	24MC	1		BN4	1	24VDC	MICROCOMPT+ POWER SUPPLY
						0MC	2	2		0V		
						Security	3	3		RELAY	SECURITY	Safety request
						Author.	4	4		EV 3/2NC	AUTHOR.	Authorisation
						HS	5	5		RELAY	HS	High speed
						PTO	6	6		EV 3/2NC	PTO	Power take off
						Stop	7	7		RELAY	MS	Motor Stop
						DC	8	8		EV 3/2NC	DC	Declutching (or High Speed)
						FV	9	9		EV 3/2NC	FV	Footvalve
								V/J				
				●		ARU	Bc/Nr	BN5	1			Relier 1(BN5) à 5 (BN6)
				●		M.SW	-	BN6	5			Relier 1(BN5) à 5 (BN6)

*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN L LPG-TRONIC

This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° '' ''')
Temperature: °C

Pneumatic wiring control box RC LYNX version




Label	Input	Output	Function	Observation
Air supply	X		Main supply of the control box + detector for pressure drop	Pressure >1 bar: green warning light Pressure <1 bar: orange warning light. Disable the security management for trunk, pressure drop and customer ARU
	X		Secondary supply of the control box	The 6 bar-calibrated regulator, the 6/4 reducer and the Ø4 coupling are packed in a bag inside the control box
Air from parking brake	X		Air from parking brake	
Exhaust		X	Exhaust	Put a tube L=100mm min. (no muffler)
Emergency stop*		X	Pneumatic emergency stop	
Declutching		X	Declutching actuator (or High speed)	With pneumatic declutching
Footvalve		X	Footvalve opening	
Power take off PTO or Authorisation		X	Power take off or Authorisation	Power take off: leave the plug in place and don't connect any tube in case of electrical control Authorisation: hydraulic control
ARU Emergency stop input	X		Detection of emergency stop requests	ARU are connected in series in a positive safety loop
Trunk	X		Detection of back trunk openings	No air=trunk opened
MS*		X	Timed Master switch	When using the MS pneumatic output
Supply MS*	X		Master switch air supply	When using the MS pneumatic output

*Unused ports must be plugged.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 36 / 54

5.6. ELECTRICAL WIRING WITH CONTROL BOX AND ASKW REMOTE CONTROL




Terminal assignment of the MICROCOMPT+ power supply board ASKW version

Any mass braids and shielding must be connected to the MICROCOMPT+ ground bar

TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

POWER SUPPLY BOARD



EQUIPMENTS CONNECTED TO THE MICROCOMPT+								POWER SUPPLY BOARD			
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function		Observation
		No.	CG*	Alma	Type						
	CONTROL BOX serial links	C6		●	ADR 12x0.34 sh.	Rx	Vt	1	Tx	PRINTER	Serial link RS232 Embedded computing (EC) Remote control (RC)
						Tx	Jn	2	Rx		
						0V	Nr	3	0V		
						Rx	Bl	4	Tx	RS232 EC + RC	
						Tx	Rg/Bl	5	Rx	RS485 EC + RC	
						RS485 +	Bc	9	RS485+		
						RS485 -	Rs	10	RS485-	Serial link RS485 Embedded computing (EC) Remote control (RC)	
						Pulses output +	Rg	22	S		PULSES OUTPUT
						Pulses output -	Gr	24	0V		
						Mesur. End	Vi	53	24VDC	MEASURING END	Anti- fraud, Final stop
PTO control	Mr	58	PTO	PTO CONTROL							
	TURBINE TRANSMITTER	C3	1/2"NPT		ADR 4x0.34 sh.	12V	Jn	11	12V	TURBINE INPUT	Connect the shielding
						V1	Mr	12	V1		
						V2	Vt	13	V2		
						0V	Bc	14	0V		
	RECEIVER ASKW (PLC) Commands	C5		●	12G1	24VDC	1	25	24VDC	POWER SUPPLY 24VDC	High speed Authorisation Intermediate stop Measuring end
						0V	2	26	0V		
						HS	3	74	24VDC	HIGH SPEED	
						Author.	4	75	24VDC	AUTHOR.	
						Intermediate stop	5	49	24VDC	INTERM. STOP	
						Measuring end	6	50	24VDC	MEASURING END	
	Pt1000 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100	Connect the shielding
						-	Bc	34	-		
						-	Vt	35	-		

*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN L LPG-TRONIC

This document is available at www.alma-alma.fr

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

Page 38 / 54

Control box LPG-TRONIC

Customer cable gland:
- 2 PG13 cable Ø6-12
- 1 PG09 cable Ø4-8

Pneumatic block

Pneumatic indicator
(presence air brake park)

Emergency stop from customer

From Trunk

Air supply

From parking brake

M (1 : 2)

Luminous power button

Vent plug
(do not block)

3 Sub-D 9pts male

Regulator calibrated at 6 bar
and fittings packed in bag

Print cable L=5m
power supply and RS232

Technical features

- Box (No ATEX): 250x200x159 material ABS with transparent lid.
- Protection level : IP50
- Temperature: -10° to +60°C
- Mass (except wiring): about 3.2 kg
- Electrical part:
 - Input power 24Vcc (truck).
 - Customer terminal block BN3: 1.5mm² max.
 - Solenoid valves control: 24Vdc ±10% - 1.2W
- Pneumatic part:
 - Pneumatic (4 output 3/2NC).
 - Fluid: 40µm filtered air lubricated or not
 - Operating Pressure: 10 bar max.
 - Flowrate at 6 bar: 500 NI/min.
 - Pneumatic fittings: for tube Ø6.
 - Unused outputs must be plugged.

DESCRIPTION OF MODIFICATION 686:
Changing the start button label

PRESENTATION DRAWING		DEF045
Control box		
907	PPN045	E 9 / 10
Dev N°	Drawing N°	Rev Folio
		Created on : 05/06/2012
		Modified on : 18/09/2019
		by EG
		ROC verified by
		CHR XS


NOTE: Overall dimensions on next folio

Document available on website www.alma-alma.fr

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	
	This document is available at www.alma-alma.fr	Units of measure: Length: mm Angle: degree (° '' ''') Temperature: °C
Page 39 / 54		



Electrical wiring control box ASKW version

Wiring diagram of the control box ASKW version:



Configuration of switches:

PTO (Power take off), Motor stop (AR MOT), High speed (GD. VIT.), RC LYNX, Truck trunk (COFFRE), Master Switch (M. SW), SW9 and SW13:

		
Linear switching element for relays NC or NO contact	Three-position switch for common contact of the relay: 1 → 24VDC 2 → GND (0V) 3 → CS (Free contact)	SW9 → DEBR. (Declutching) or GD. VIT. (H. speed) for semi trailer SW13 → 24V for PTO or AUTOR for semi trailer

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° + ') Temperature: °C
	This document is available at www.alma-alma.fr	Page 41 / 54


TERMINAL ASSIGNMENT OF THE CONTROL BOX ASKW VERSION



EQUIPMENT CONNECTED TO THE CONTROL BOX								CONTROL BOX TERMINAL BLOCKS					
Option	Equipement	Cable for information)				Function	Colour or No.	Block	Terminal	Function		Observation	
		N°	CG*	Alma	Type								
	MICROCOMPT+ Serial links	C6			12x0.34 sh	Tx	Vt	BN1	1	Rx	PRINTER	RS485 serial link Embedded computing (EC) Remote control (RC)	
						Rx	Jn		2	Tx			
						0V	Nr		3	0V			
						RS485 -	Rs		4	RS485	EC + RC		RS232 serial link Embedded computing (EC) Remote control (RC)
						RS485 +	Bc		5				
						Tx	Bl		10	RS232	EC + RC		
						Rx	Rg/Bl		11				
	PRINTER	C1		●	2x1	Rx	Vt	BN2	1	Rx	PRINTER		
						Tx	Jn		2	Tx			
						0V	Mr		3	0V			
						24VDC	Bc		4	24VDC			
	POWER SUPPLY					24VDC		BN3 - Bornier client	1	24VDC	POWER SUPPLY	24VDC truck battery (after battery switch and protected by a fuse)	
					0V		2		0V				
	POWER SUPPLY REMOTE CONTROL				24VDC		3		24VDC	POWER SUPPLY RC			
	RC LYNX BELL				0V		4		0V				
	MOTOR STOP								5	-	-		
									6	24VDC/0V/CS	MOTOR STOP	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact	
	PTO								7	CS			
									8	24VDC/0V/CS	PTO	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact	
	HIGH SPEED								9	CS			
									10	24VDC/0V/CS	HIGH SPEED	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact	
	PTO CONTROL								11	CS			
									12	-	-		
TRUCK TRUNK									13	CS	TRUCK TRUNK	Relay Only used with configuration Free contact	
									14	24VDC/0V/CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact)	
	RECEIVER ASKW (PLC)	C7		●	12G1	24VDC	10	BN3	3	24VDC	POWER SUPPLY RC	Fuse	
						0V	11		4	0V			
						24VDC	1	BN4	1	24VDC	MICROCOMPT+ POWER SUPPLY		
						0V	2		2	0V			
						Author.	4		4	EV 3/2NC	AUTHOR.	Authorisation	
						HS	5		5	RELAY	HS	High speed	
						PTO	6		6	EV 3/2NC	PTO	Power take off	
						Stop	7		7	RELAY	MS	Motor Stop	
						DC	8		8	EV 3/2NC	DC	Declutching (or High Speed)	
						FV	9		9	EV 3/2NC	FV	Footvalve	
						Security	3	BN6	5	RELAY	SECURITY	Safety request	
						V/J							


*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 42 / 54


TERMINAL ASSIGNMENT OF THE ASKW RECEIVER (PLC)												
												
EQUIPMENT CONNECTED TO THE ASKW							TERMINAL BLOCK OF THE PLC FOR ASKW					
Option	Equipement	Cable (for information)				Function	Colour or No.	Block	Terminal	Function		Observation
		N°	CG*	Alma	Type							
	MICROCOMPT+ Commands	C5			12G1	24VDC	1	C7	1	24VDC		Connect to C7
						0V	2	C7	2	0V		Connect to C7
						HS	3		I2	HS		High speed
						Author.	4		I1	AUTHOR.		Authorisation
						Interm. Stop	5	Q1	2	INTERMEDIATE STOP		Intermediate stop
						Measur. End	6	Q2	2	MEASURING END		Measuring end
	CONTROL BOX Commands	C7			12G1	EV Emergency	3	MAQ4	2	SAFETY REQUEST		Emergency stop
						EV Author.	4		I1	AUTHOR.		Authorisation
						Relay HS	5	MAQ1	2	HS		High speed
						EV PTO	6	MAQ2	I5	PTO		CONTINUOUS Power take off
									2			PULSE Power take off
						Relay MS	7	Q3	2	MS		Motor Stop
						EV DC	8	MAQ3	2	DC		Declutching
						EV FV	9		I6	FV		Footvalve
						24VDC	10	Q3	L1	24VDC	BOARD 24V-SUPPLY	
								Q4	1			
								MAQ1	1			
								MAQ2	1			
								MAQ3	1			
								MAQ4	1			
						0V	11	MA	L1	0V		
								Q1	1			
								Q2	1			
								MA	N			
						Parking brake		MA	I2	24VDC	Parking brake	Present: +24VDC Absent: No authorisation
								MA	I4			

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 44 / 54

Pneumatic wiring control box ASKW version



*Unused ports must be plugged.

6. METERING LINE GPL-BALC

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




INSTALLATION GUIDE DI 005 EN L LPG-TRONIC

This document is available at www.alma-agma.fr

Units of measure:
Length: mm
Angle: degree (° '' ''')
Temperature: °C

6.1. INSTALLATION AND SEALING RECOMMENDATIONS ADRIANE TURBINE METER

- The identification plate and the led of the pulse emitter(s) shall be visible and accessible.
- The turbine must be installed with respect to the flow direction.
- Put sealing rings each other sides between the turbine and the backflanges.
- Leave an open space all around the turbine in order to ease maintenance.
- Install a 400 μ filter (mini) on the pipe upstream from the turbine meter.
- After installation or during the commissioning period, if the new or modified pipes have not been perfectly cleaned or pickled and passivated, the turbine should be protected by a honeycomb sieve – max. 1mm mesh. It must be placed between two flanges upstream from the turbine.
- Dimensions: A > 100mm.



- Refer to the certificate written on the identification plate of the measuring system to suit the sealing requirements
- No loose lead wire on the sealing devices



For accuracy class 0.5 and 1.0 measuring systems, the pipes and equipment upstream or downstream the turbine meter must have the same nominal diameter as the meter on a length at least equal to 10 times this diameter upstream and 5 times this diameter downstream.

These lengths can be straight or bent.

It is mandatory that no flowrate adjustment device (e.g. a variable-opening valve) is located upstream at a distance less than 10 times the nominal diameter of the meter: Do not create derivation circuits with sample or bypass, specially make sure that no nozzle is present on this pipe.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN L LPG-TRONIC

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

This document is available at www.alma-alma.fr

Page 48 / 54

7. PRINTER

180

101.5

190

Switch ON/OFF

Switch SW1
(under printer)

D-Sub connector 25 pin female

24Vdc connector

D-Sub connector 25 pin female

Switch 3 ON

D-Sub connector 25 pin female

Switch SW1
(under printer)

D-Sub connector 25 pin female

Technical data:

- Power supply : 24Vdc $\pm 10\%$
- Current consumption (at 24V) :
 - Mean : approx. 600mA
 - Peak : approx. 5.5A
- Standby : approx. 100mA
- Temperature : $+5^{\circ}\text{C}$ to $+40^{\circ}\text{C}$
- Mass: 1.6 kg

DO NOT EXPOSE THE PRINTER TO ANY HEAT-SOURCE, AND PROTECT IT FROM VIBRATIONS AND FROM WATER PROJECTIONS.

IF IT'S NOT IN THE TRUCK CABIN, THE PRINTER MUST BE INSTALLED IN A TIGHT BOX IN ORDER TO FACILITATE INTRODUCTION AND EXTRACTION OF PAPER.

PRESENTATION DRAWING PPN901
Flatbed printer
TM-U295


907 Dev N° Drawing N° Rev 2/2 Folio 11/01/2019 Modified on : 24/03/2010 Created on : 11/01/2019 by CC verified by SR XS

Service Development 13127 Vitrolles
www.alma-alma.fr
Code : 6176
DEV N° : 907
Drawing N° associated with the related CEI file
Metro : -
ATEX: -

Document available on website [alma-alma.fr](http://www.alma-alma.fr)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (°) " Temperature: °C
	This document is available at www.alma-alma.fr	Page 49 / 54


-
- Technical drawings of the 3D printer showing dimensions A, B, C, and D. Dimension A is the height of the printer. Dimension B is the width of the printer. Dimension C is the length of the printer with the filament spool holder. Dimension D is the length of the printer without the filament spool holder.



DO NOT EXPOSE THE PRINTER TO ANY HEAT-SOURCE.
PROTECT IT FROM VIBRATIONS AND WATER PROJECTIONS.


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° + ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 50 / 54

8. CONVERTER 24VDC/24VDC 2.1A 50W



Document available on website [alma-alma.fr](http://www.alma-alma.fr)

9. TEMPERATURE PROBE Pt100 – CT1001



- **Mass:** ~350g without thermowell,
 - **Temperature range:** -20°C to +50°C,
 - **EX-type examination certificate:** INERIS 04 ATEX 026
 - **Ex Protection:** Ex ma II T4 Ga

The sensor body is made of bronze color anodized aluminum alloy;
 The ring and the nut are made of brass.
 The probe can be mounted either on a ALMA thermowell or on a
 thimble connection 1/4 "BSP (M10x1 n5).
 Before installation, lubricate the parts in contact with the thermowell or
 the boss, to prevent corrosion.

PT100 features:

- 3 wires
- 1/3 DIN

*ATEX "ma" certification.
 For installation and use in hazardous areas see Instruction manual

Also available with output connector according to IEC 60947-5-2

Function	Marking on the wire	Color wire
PT100/1	1	Yellow
PT100/2	2	White
PT100/3	3	Green

 Service Development 13127 Vitrolles		PRESENTATION DRAWING DFV042		Description of the amendment N°662 Removal of the apparent 5mm requirement on the wiring	
DEV N° : 949d Code : 8151		Temperature probe CT1001-Pe			
Drawing N° associated with the related CET file		949d	PPV042	L	5 / 6
Metro :		Dev N°	Drawing N°	Rev	Folio
ATEX :		INERIS 04 ATEX 0026			
		Modified on :	29/03/2019	by	CHR
		Created on :	13/09/2003	BM	verified by
					CC
					BM

Document available on website alma-alma.fr

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	Units of measure: Length: mm Angle: degree (° " ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 52 / 54



ADRIANE DP-20-SB Type 283.110x110
 Serialised Pressure Transmitter (AI) 10...12 V
 4-wire output signal: 0...20 mA


	A/Nr.	B/Nr.
Version	000000	000000
Material	Alu	Alu
Pressure range	0...10 bar	0...10 bar
Output	0...20 mA	0...20 mA
Power supply	10...12 V	10...12 V
Process	Water	Water
Ex version	Ex	Ex
Accessories	-	-

CE mark and other certification details are also visible on the label.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN L LPG-TRONIC	<u>Units of measure:</u> Length: mm Angle: degree (° + ") Temperature: °C
	This document is available at www.alma-alma.fr	Page 53 / 54

10. KIT FOR MEASURING SYSTEM IDENTIFICATION PLATE

The identification plate shall be clearly installed, near the associated indicator device, and of easy access in order to be able to read features and to stamp the regulatory marks.



The security screws of the cups (provided by ALMA) must be screwed in the tap of the frame (do not use removable nuts).

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



INSTALLATION GUIDE DI 005 EN L
LPG-TRONIC

Units of measure:
Length: mm
Angle: degree (° ' ")
Temperature: °C

This document is available at www.alma-alma.fr

Page 54 / 54