


INSTALLATION GUIDE

DI 005 EN N  
LPG-TRONIQUE


Described in EC-type examination certificate N°: LNE-13621

N	2024/10/24	Modification of Installation and sealing drawing	ITB	
M	2023/10/23	Corrections on the electrical wiring	ITB	NC
J	2020/10/12	Corrections on the electrical wiring of the LYNX version	DSM	MV
K	2019/12/10	Connectivity [PJA129], Drawings update	DSM	MV
J	2019/02/26	Configuration of the RCT4 switches, New FORM DOC, Drawings update	DSM/CHR	SR
Issue	Date	Nature of modifications	Written by	Approved by


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 1 / 55

# CONTENTS

<b>1. GENERAL RECOMMENDATIONS .....</b>	<b>4</b>
1.1. MECANICAL RECOMMENDATIONS .....	4
1.2. ELECTRICAL RECOMMENDATIONS .....	5
1.3. PNEUMATIC RECOMMENDATIONS .....	7
<b>2. GENERAL PRESENTATION .....</b>	<b>8</b>
2.1. USE ACCORDING TO MID CERTIFICATE .....	8
2.2. SPECIAL CONDITIONS FOR INSTALLATION IN ANY CASES .....	8
<b>3. PART LIST .....</b>	<b>9</b>
<b>4. INSTALLATION AND SEALING DRAWING OF THE LPG-TRONIC .....</b>	<b>11</b>
<b>5. CALCULATOR-INDICATOR MICROCOMPT+ .....</b>	<b>13</b>
5.1. INSTALLATION RECOMMENDATIONS CALCULATOR-INDICATOR MICROCOMPT+ .....	14
5.2. ELECTRICAL WIRING CALCULATOR-INDICATOR MICROCOMPT+: BASIC VERSION .....	15
Terminal assignment of the MICROCOMPT+ power supply board basic version .....	16
Connection of the network board – Ethernet, RS232/485, CANBus .....	17
Wiring diagram of the 24VDC/24VDC converter for printer .....	18
5.3. GSM/GPS MODULE EQUIPPED – 2-ANTENNA BOX .....	19
Mounting and wiring of the GSM and GPS antennas .....	20
Mounting of the GSM/GPS cables into the cable glands .....	21
Wiring of the 2-antenna box to the MICROCOMPT+ .....	21
5.4. ELECTRICAL WIRING WITH CONTROL BOX AND RCT4 REMOTE CONTROL .....	22
Terminal assignment of the MICROCOMPT+ power supply board RCT4 version .....	23
Control box LPG-TRONIC .....	24
Electrical wiring control box RCT4 version .....	26
Pneumatic wiring control box RCT4 version .....	28
Remote control RCT4 .....	29
Electrical wiring RCT4 remote control receiver .....	30
5.5. ELECTRICAL WIRING WITH CONTROL BOX AND RC LYNX REMOTE CONTROL .....	31
Terminal assignment of the MICROCOMPT+ power supply board RC LYNX version .....	32
Control box LPG-TRONIC .....	33
Electrical wiring control box RC LYNX version .....	35
Pneumatic wiring control box RC LYNX version .....	37
5.6. ELECTRICAL WIRING WITH CONTROL BOX AND ASKW REMOTE CONTROL .....	38
Terminal assignment of the MICROCOMPT+ power supply board ASKW version .....	39
Control box LPG-TRONIC .....	40
Electrical wiring control box ASKW version .....	42
Electrical wiring ASKW remote control receiver/PLC .....	44
Pneumatic wiring control box ASKW version .....	47
<b>6. METERING LINE GPL-BALC .....</b>	<b>48</b>
6.1. INSTALLATION AND SEALING RECOMMENDATIONS ADRIANE TURBINE METER .....	49
<b>7. PRINTER .....</b>	<b>50</b>
7.1. INSTALLATION RECOMMENDATIONS PRINTER .....	51

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	
		Page 2 / 55

<b>8. CONVERTER 24VDC/24VDC 2.1A 50W .....</b>	<b>52</b>
<b>9. TEMPERATURE PROBE PT100 – CT1001 .....</b>	<b>53</b>
9.1. INSTALLATION RECOMMENDATIONS TEMPERATURE PROBE.....	54
<b>10. KIT FOR MEASURING SYSTEM IDENTIFICATION PLATE.....</b>	<b>55</b>


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 3 / 55


## 1. GENERAL RECOMMENDATIONS

**IN ORDER TO AVOID ALL THE PROBLEMS CONCERNING THE INSTALLATION, THE OPERATION AND THE MAINTENANCE OF THE EQUIPMENTS, BEING ABLE TO CREATE INOPPORTUNE FAILURE, PLEASE RESPECT THE FOLLOWING RECOMMENDATIONS.**

**BEFORE ANY WORK, MAKE SURE THAT THE EQUIPMENTS ARE NOT POWERED.**


### 1.1. MECANICAL RECOMMENDATIONS

- ⇒ Respect the recommendations of the instruction manual specifying the installation, operation and maintenance conditions of the ATEX equipment (instruction manual supplied with the equipment).
- ⇒ Take care to place the equipment in order to facilitate their installation, operation and maintenance by the technicians (working ergonomics).
- ⇒ Take care to position properly the equipment; the display must be readable without any difficulty.
- ⇒ Apply a tightening torque suitable with size and material of the fixation element except particular specifications mentioned on the presentation drawing or in the installation guides.
- ⇒ Mechanically protect the cables with the corrugated conduit if the cables are not ADR (corrugated conduit adapted to vehicles used for 'carriage of dangerous goods of road' - hydrocarbons, LPG ... - and meet the requirements of French standard NF R13-903. Refer to the regulations in force).
- ⇒ Ensure there are a good mechanical strength and a good sealing between cable glands and cables, and between cable glands and corrugated conduit.
- ⇒ Respect cables and corrugated conduit radii of curvature.
- ⇒ Leave enough flexibility to wires in order to avoid any risk of stripping.
- ⇒ Allow the drainage of the water in the lower loop (siphon) of the corrugated conduit (not water retention inside the corrugated conduit).
- ⇒  See § INSTALLATION AND SEALING RECOMMENDATIONS ADRIANE TURBINE METER.


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 4 / 55

## 1.2. ELECTRICAL RECOMMENDATIONS

- ⇒ According to the ATEX directive or any other regulations in force in the country of destination, the safety protection level of the equipment must agree with the installation area (potentially explosive atmospheres).
- ⇒ Respect the recommendations of the instruction manual specifying the installation, operation and maintenance conditions of the ATEX equipment (instruction manual supplied with the equipment).
- ⇒ Connect the supply of the equipment downstream cut-out, on the power supply reserved to the measured distribution.
- ⇒ Put a delayed protection of 5A upstream the 24VDC supply to protect equipment in case of reverse polarity or overcurrent.
- ⇒ Use ADR specific cable, if it is not the case, use at minimum a cable resisting to hydrocarbons. Mechanically protect this cable with a corrugated conduit (corrugated conduit adapted to vehicles used for 'carriage of dangerous goods by road' - hydrocarbons, LPG ... - and meet the requirements of French standard NF R13-903. Refer to the regulations in force).
- ⇒ Take care not to damage the terminals of the different electronic boards while wiring.
  - Screw terminals: do not damage the screw heads of the terminals.
    - Use insulated lugs and insulated wire ferrules adapted to the section of wires.
  - Spring terminals: do not block the springs (if a spring is blocked, the electronic board must be replaced).
    - Use flat screwdriver 0.4x2.5 (see fig.1).
    - Insert the screwdriver slightly tilted, then push it perpendicularly to the terminal.
    - Do not exceed the upright position when the screwdriver is down in order not to block the spring.
    - Insert or remove the wire and remove the screwdriver.



- ⇒ Pass the power supply cores (24VDC truck) through the ferrites by carrying out a loop (ALMA supply).
- ⇒ Do not use wires of section higher than 1.5mm<sup>2</sup>.
- ⇒ Do not insert more than two wires in a terminal, if necessary use an insulated twin wire ferrule (unless otherwise indicated).
- ⇒ Strictly respect the polarities of the input/output when wiring, in accordance with serigraphy on the cards and/or with the installation guide indications.
- ⇒ Whenever possible, perform a wired test, after wiring and before powering.
- ⇒ Whenever possible, respect the locations of the cables specified in the installation guide.
- ⇒ Equipment must be connected to the frame ground (external ground connection).
- ⇒ Whenever possible, use shielded cables with a 360° connection through the metal cable glands (see the documentation delivered with the equipment).  
Otherwise, connect the shields to devices inside the equipment (ground terminal, earth bar, earth boss...).
- ⇒ Whenever possible, label the cables and cores according to the installation guide to facilitate the later maintenance operations.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 5 / 55

- ⇒ Respect a homogeneous wire color code.
- ⇒ Printer TMU295: before positioning the printer on its support, check that configuration switches of the data link protocol, located under the printer, are well positioned: No3 on 'ON' and the 7 others on 'OFF'.
- ⇒ Current of the electrical devices:

Electrical devices	Supply voltage	Minimum current	Maximum current
MICROCOMPT+	24VDC +/-10%	0.7 A	1.5 A
PRINTER	24VDC +/-10%	0.1 A	5.5 A (switch-on)

- ⇒ Color code according to DIN 47100.
- ⇒ Code for designation of colours according to IEC 60757 (except FR codes):

FR				EN	IT	ES	DE
Couleurs	Codes		Standard codes CEI 60757	Colours	Colori	Colores	Farbe
Blanc	<b>Bc</b>		<b>WH</b>	White	Bianco	Blanco	Weiß
Marron	<b>Mr</b>		<b>BN</b>	Brown	Marrone	Marrón	Braun
Vert	<b>Vt</b>		<b>GN</b>	Green	Verde	Verde	Grün
Jaune	<b>Jn</b>		<b>YE</b>	Yellow	Giallo	Amarillo	Gelb
Gris	<b>Gr</b>		<b>GY</b>	Grey	Grigio	Gris	Grau
Rose	<b>Rs</b>		<b>PK</b>	Pink	Rosa	Rosa	Lila
Bleu	<b>Bl</b>		<b>BU</b>	Blue	Blu	Azul	Blau
Rouge	<b>Rg</b>		<b>RD</b>	Red	Rosso	Rojo	Rot
Noir	<b>Nr</b>		<b>BK</b>	Black	Nero	Negro	Schwarz
Violet	<b>Vi</b>		<b>VL</b>	Violet	Viola	Violeta	Violett
Orange	<b>Or</b>		<b>OG</b>	Orange	Arancio	Naranja	Orange
Vert/Jaune	<b>V/J</b>		<b>GNYE</b>	Green/Yellow	Verde/Giallo	Verde/Amarillo	Grün/Gelb


### 1.3. PNEUMATIC RECOMMENDATIONS

- ⇒ Air must be filtered – from 40 to 20µm. Specific recommendations may be added in the installation guides or on the presentation drawings.
- ⇒ The air lubrication must be permanent and correct to avoid any damage on the pneumatic components.
- ⇒ The air supply pressure to the inlet of the equipment must be at least 6 bar and max 8 bar. Specific recommendations may be added in the installation guides or on the presentation drawings.
- ⇒ The pneumatic supply pipes (6/4) must be cut straight (no slanting cut) and should not be crushed after cutting to prevent leakage on fittings.
- ⇒ Respect the radii of curvature of the pneumatic pipes indicated by the manufacturer.
- ⇒ Use colored pneumatic pipes to ease maintenance operation.
- ⇒ In no case the exhaust holes of the pneumatic organs should be plugged, obstructed, unless if that is clearly specified in the installation guides or on presentation drawings.
- ⇒ The use of muffler is not allowed under any circumstances (fouling, frost...). Put a pneumatic pipe of sufficient length, pointed downwards, so that its end is placed in a protected area (L = 100 mm min.).
- ⇒ Pressure unit conversion:

PRESSURE UNIT CONVERSION				
Unités	Bar	PSI	Pascal	kg/cm <sup>2</sup>
1 Bar =	1	14,5	100 000 (1x10 <sup>5</sup> )	1,0197
1 PSI =	0.069	1	6894,5	0,07031
1 Pascal =	1x10 <sup>-5</sup>	14,5x10 <sup>-5</sup>	1	1,0197x10 <sup>-5</sup>
1 kg/cm <sup>2</sup> =	0,98	14,22	98066,5	1

PSI = Pound per Square Inch (livre par pouce carré)

1 bar = 100 kPa = 0.1 MPa (1 MPa = 10 bar)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 7 / 55

## 2. GENERAL PRESENTATION


### 2.1. USE ACCORDING TO MID CERTIFICATE

The LPG TRONIC measuring system is covered by the EU type examination certificate N° LNE-13621. Refer to this certificate for any precision about its installation.

For the sealing plan, see Annex to EU type examination certificate N° LNE-13621.






### 2.2. SPECIAL CONDITIONS FOR INSTALLATION IN ANY CASES

- ⇒ Safety valves may be incorporated in the ALMA LPG-TRONIC measuring system. If they are located downstream of the turbine meter, they must open to the atmosphere or be connected to the receiving tank. In no case may safety valves located upstream of the turbine meter be connected to the valves located downstream by pipes that bypass the turbine meter.
- ⇒ To prevent any hydraulic connection of bottle under pressure, the purge below the gas separator must finish on a smooth stiff pipe, without threading nor join, and which is not take down.
- ⇒ The ON/OFF inputs on the power supply board are activated by supplying a 0V. This can be done, for example, by a relay or a switch.
  - 0V : Activated entry
  - No current signal : Non activated entry


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 8 / 55




3. PART LIST


EQUIPMENTS INCLUDED IN THE MEASURING SYSTEM DELIVERED BY ALMA				
Item	Equipment	Designation	Qty	Option*
1		<b>CALCULATOR INDICATOR MICROCOMPT+ LPG TRONIC WITH Bluetooth CONNECTION</b>	1	
		<b>Wi-Fi CONNECTION</b> (As an alternative to Bluetooth)		•
		<b>RFID SUPERVISOR KEY</b>		
2		<b>GPL TRONIC CONTROL BOX</b> (Provided with RS232-serial link and power supply for printer)	1	•
3	3.a 	<b>METERING LINE GPL-BALC</b> (Gas separator – ADRIANE turbine meter DN50-30 – differential valve)	1	
	3.b 	<b>ADRIANE TURBINE METER DN50-30 BALC</b>		

Non-contractual pictures


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 9 / 55

EQUIPMENTS INCLUDED IN THE MEASURING SYSTEM DELIVERED BY ALMA				
Item	Equipment	Designation	Qty	Option*
4	<b>4a</b> 	<b>PRINTER TMU-295</b> (Printer – printer holder – cable 5 or 10m)	1	
	<b>4b</b> 	<b>CONVERTER 24VDC/24VDC 2.1A 50W</b> Provided if there is no control box (With RS232 serial link wire and 24VDC power supply for printer)	1	●
5		<b>REMOTE CONTROL RCT4</b>	1	●
6		<b>Pt100 TEMPERATURE SENSOR – CT1001-Pe</b> (Supplied with thermowell)	1	
7		<b>2-ANTENNA BOX GSM AND GPS</b>	1	●
8		<b>KIT FOR MEASURING SYSTEM IDENTIFICATION PLATE</b> (Plate and sealing device)	1	●
<b>Option*: equipment sold as an option by ALMA, it must be installed on the measuring system if required by the certificate.</b>				

Non-contractual pictures


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	
		Page 10 / 55

#### 4. INSTALLATION AND SEALING DRAWING OF THE LPG-TRONIC




#### Legend:

- Clf: Foot valve  
Pg: Line purge in the atmosphere (can be collected between them)  
Va: Control valve allowing liquid to flow.  
R1: Two-way cock for deliveries with meter and for draining or filling tank without meter. This device is optional and may be replaced by a direct connection.  
F: Filter  
Vm: Operation valve (optional).  
B: Adjustable bypass connected to tank  
Mo: Manometer (optional)  
P: Pump  
R2: Three-way cock (optional) for direct delivery without meter.  
Cla: Non-return valve fitted to block comprising filter and gas separator  
F1: Filter fitted to gas separator  
Sg: Gas separator, connected to gaseous phase of tank. If a safety valve (Vas) is fitted to this device, it must be placed between the tank and the diversion from the pressure control valve (Vamp).  
Vas: Automatic safety valve (optional)  
Th: Thermometer. The thermometer must be located close to the meter, either in the gas separator or at the meter inlet or outlet.  
C: Meter  
TT: Pt100 temperature sensor (optional).  
Vamp: Pressure control valve, regulated to maintain pressure at least 1 bar higher than saturated vapour pressure in the tank  
M: Manometer  
S: Valve of thermal expansion  
Vma: Operation valve  
VSP: Three ways faucet allowing a delivery by two ways of distribution  
FI1: Full hose  
Z: Gaseous phase piping, to be used only for filling vehicle tank or for draining tank when measuring system is verified.  
Em1: Seals ensuring the tamper-proofness of the gas separator head.  
Em2: Prevents removal of non-return valve (Cla).  
Em3: Prevents removal of gas separator.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 11 / 55

- Em4: Prevents removal of meter (C).
- Em5: Prevents removal of temperature sensor.
- Em6: Prevents removal of automatic pressure control valve (Vamp).
- Em7: Prevents removal of operation valve (Vma).
- Em8: Prevents removal of controlled selective valve (Vsp, optional).
- Em9: Prevents removal of full hose (FI1).
- Em10: Prevents removal of controlled operation valve (Vmp, optional).
- Em11: Prevents removal of automatic safety valve (Vas).

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 12 / 55

## 5. CALCULATOR-INDICATOR MICROCOMPT+



Document available on website [alma-alma.fr](http://alma-alma.fr)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




### INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)


**Units of measure:**  
 Length: mm  
 Angle: degree (° '' ''')  
 Temperature: °C

## 5.1. INSTALLATION RECOMMENDATIONS CALCULATOR-INDICATOR MICROCOMPT+


- Fasten the box with 4 M6 screws (holder suitable for vibrations and designed to support the MICROCOMPT). On the box: 4 M6 blind holes tapped length=12 over 185x132).
- Leave an open space around the box in order:
  - o To facilitate maintenance operation.
  - o To prevent any pressing on pushbuttons and on the glass.
- The space between the front face of the box and the cabinet door shall be sufficient.
- Dimensions:  $A > 100\text{mm}$  and  $B > 60\text{mm}$



- SOLUTION 1: straight box if it's a breast height.




Left hand view  
Closed box



Left hand view  
open box

- SOLUTION 2: 20° angle if it's not at breast height.



Left hand view  
Closed box



Left hand view  
open box


**REFER TO THE INSTRUCTION MANUAL**  
(DELIVERED WITH THE EQUIPMENT OR AVAILABLE ON ALMA WEBSITE)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



5.2. ELECTRICAL WIRING CALCULATOR-INDICATOR MICROCOMPT+: BASIC VERSION




ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 15 / 55

## Terminal assignment of the MICROCOMPT+ power supply board basic version

Any mass braids and shielding must be connected to the MICROCOMPT+ ground bar

### TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

#### POWER SUPPLY BOARD



EQUIPMENTS CONNECTED TO THE MICROCOMPT+								POWER SUPPLY BOARD			
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function		Observation
		No.	CG*	Alma	Type						
	PRINTER	C1	1/2"NPT	●	ADR 4x0.34 sh.	Rx	Bc	1	Tx	PRINTER	Connect the shielding
						Tx	Mr	2	Rx		
						0V	Vt	3	0V		
●	EMBEDDED COMPUTING	C6			3x0.34 sh.	Rx	Bc	6	Tx	GPS / GSM / EC	Connect the shielding
						Tx	Mr	7	Rx		
						0V	Vt	8	0V		
	TURBINE TRANSMITTER	C3	1/2"NPT		ADR 4x0.34 sh.	12V	Jn	11	12V	TURBINE INPUT	Connect the shielding
						V1	Mr	12	V1		
						V2	Vt	13	V2		
	24VDC-INPUT truck (battery)	C5 bis			2x1	Bat (+)	1	25	24VDC	POWER SUPPLY 24VDC	
						Bat (-)	2	26	0V		
	INTERMEDIATE STOP	C5			7X1	Interm. Stop	5	49	See sub-chapter 2.2	INTERM. STOP	Free contact from the vehicle automatic process
	MEASURING END					Measur. end	6	50	See sub-chapter 2.2	MEASURING END	Free contact from the vehicle automatic process
	HIGH FLOWRATE					HF	3	74	24VDC	HIGH SPEED	24VDC- output to the vehicle automatic process
	AUTHORISATION CHANNEL 1					Author.	4	75	24VDC	AUTHOR. CHANNEL 1	Connect the 24VDC- output in series with the vehicle automatic process
	AUTHORISATION CHANNEL 2					Author.	7	63	24VDC	AUTHOR. CHANNEL 2	Connect the 24VDC- output in series with the vehicle automatic process
	Pt100 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100	Connect the shielding
						-	Bc	34	-		
						-	Vt	35	-		

\*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



### INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C


Page 16 / 55



## Connection of the network board – Ethernet, RS232/485, CANBus

Connection to the Ethernet network:

- With the RJ45 connector according to the EIA/TIA-568 standard
- Or with the screw-terminal: see details in the table below.



Cable clips

**NETWORK BOARD**

Ethernet RJ45

RS232 or RS485 Switch

NETWORK CONNECTION TYPE								NETWORK BOARD			
Option	Connection	Cable (for information)				Function	Coulor or No.	Coulor	Function		Observation
		No.	CG*	Alma	Type						
	ETHERNET NETWORK						Vt/Bc	Tx+	Ethernet	Or connection with RJ45 according to EIA/TIA- 568	
							Vt	Tx-			
							Or/Bc	Rx+			
							Or	Rx-			
							Sh				
	RS232 or RS485							Tx / A	RS232 or RS485	Depending on the switch configuration See above	
								Rx / B			
								GND			
	CANBus NETWORK							CAN+	CANBus		
								CAN-			
								GND			

*\*Refer to the Cable Glands Installation Instructions*

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




### INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C

Page 17 / 55


### Wiring diagram of the 24VDC/24VDC converter for printer



ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY


THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION

5.3. GSM/GPS MODULE EQUIPPED – 2-ANTENNA BOX




Document available on website [alma-alma.fr](http://alma-alma.fr)

Mounting and wiring of the GSM and GPS antennas



The 2-antenna board is supplied with a micro-SIM card mounted as follows:




ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 20 / 55

### Mounting of the GSM/GPS cables into the cable glands

ALMA connects the GSM and GPS antenna to the MICROCOMPT+ (2-antenna board).



At the outlet of the MICROCOMPT+ box, you must pass both cables through cable glands. In case of an ATEX MICROCOMPT+, cable glands must be ATEX.



RECOMMENDED CABLE GLANDS  
(FOR INFORMATION ONLY)

Into the MICROCOMPT+, adjust the cable length to easily open and close the cover. Make sure to prevent damage to the cable.

Tighten both cable glands.

### Wiring of the 2-antenna box to the MICROCOMPT+

Fasten the box. You must install it in an area free of metallic cover to have a good reception and broadcasting of signal. You can install the box in a horizontal or vertical position.

Put each coaxial cable through the heat shrink sleeve.

Plug the RG58<sup>(1)</sup> cable from the MICROCOMPT+ with the RG174<sup>(2)</sup> cable from the antenna box and tighten them. Isolate the male/female SMA connectors with the supplied heat shrink sleeve (both antennas in the box are the same, cables don't have to be labelled).

Position and heat up the sleeve on the connectors to prevent corrosion and humidity.



**WARNING:** The cables of this box can be **neither shortened nor extended**

<sup>(1)</sup> RG58: Semi-rigid coaxial cable, 5mm diameter

<sup>(2)</sup> RG174: Flexible coaxial cable, 2.7mm diameter

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE


This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C

Page 21 / 55



5.4. ELECTRICAL WIRING WITH CONTROL BOX AND RCT4 REMOTE CONTROL




## Terminal assignment of the MICROCOMPT+ power supply board RCT4 version

Any mass braids and shielding must be connected to the MICROCOMPT+ ground bar

### TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

#### POWER SUPPLY BOARD



EQUIPMENTS CONNECTED TO THE MICROCOMPT+								POWER SUPPLY BOARD				
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function		Observation	
		No.	CG*	Alma	Type							
	CONTROL BOX serial links	C6		●	ADR 12x0.34 sh.	Rx	Vt	1	Tx	PRINTER	Serial link RS232 Embedded computing (EC) Remote control (RC)	
						Tx	Jn	2	Rx			
						0V	Nr	3	0V			
						Rx	Bl	4	Tx	RS232 EC + RC		Serial link RS485 Embedded computing (EC) Remote control (RC)
						Tx	Rg/Bl	5	Rx			
						RS485+	Bc	9	RS485+	RS485 EC + RC		
						RS485-	Rs	10	RS485-			
						Pulses output +	Rg	22	S	PULSES OUTPUT		
						Pulses output -	Gr	24	0V			
						Mesur. End	Vi	53	24VCC	MEASURING END		
PTO control	Mr	58	See sub-chapter 2.2	PTO CONTROL								
	TURBINE TRANSMITTER	C3	1/2"NPT		ADR 4x0.34 sh.	12V	Jn	11	12V	TURBINE INPUT	Connect the shielding	
						V1	Mr	12	V1			
						V2	Vt	13	V2			
						0V	Bc	14	0V			
	RECEIVER RCT4 Commands	C5		●	12G1	24VDC	1	25	24VDC	POWER SUPPLY 24VDC	High speed Authorisation Intermediate stop Measuring end	
						0V	2	26	0V			
						HS	3	74	24VDC	HIGH SPEED		
						Author.	4	75	24VDC	AUTHOR.		
						Interm. stop	5	49	See sub-chapter 2.2	INTERM. STOP		
						Measuring end	6	50	See sub-chapter 2.2	MEASURING END		
	Pt1000 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100	Connect the shielding	
						-	Bc	34	-			
						-	Vt	35	-			

\*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C

Page 23 / 55

## Control box LPG-TRONIC

**Customer cable gland:**  
- 2 PG13 cable Ø6-12  
- 1 PG09 cable Ø4-8

**Pneumatic block**

**Pneumatic indicator (presence air brake park)**

**M (1 : 2)**  
Emergency stop from customer  
From Trunk  
Air supply  
From parking brake

**3 Sub-D 9pts male**

**Regulator calibrated at 6 bar and fittings packed in bag**

**Luminous power button**

**Vent plug (do not block)**

**Print cable L=5m power supply and RS232**

**Technical features**  
- Box (No ATEX): 250x200x159 material ABS with transparent lid.  
- Protection level : IP50  
- Temperature: -10° to +60°C  
- Mass (except wiring): about 3.2 kg  
- Electrical part:  
- Input power 24Vcc (truck).  
- Customer terminal block BN3: 1.5mm<sup>2</sup> max.  
- Solenoid valves control: 24Vdc ±10% - 1.2W  
- Pneumatic part:  
- Pneumatic (4 output 3/2NC).  
- Fluid: 40µm filtered air lubricated or not  
- Operating Pressure: 10 bar max.  
- Flowrate at 6 bar: 500 NI/min.  
- Pneumatic fittings: for tube Ø6.  
- Unused outputs must be plugged.

**PRESENTATION DRAWING DFN045**  
Control box  
GPL-Tronique

**Service Development**  
13127 Vitrolles  
www.alma-alma.fr

DEV N° : 907 Code : 1073  
Drawing N° associated with the related CERT file  
Metro :  
ATEX:

907 Dev N°  
PPN045 Drawing N°  
E 9 / 10 Modified on : 18/09/2019  
Folio Created on : 05/06/2012

by EG  
ROC verified by  
CHR XS

**NOTE:** Overall dimensions on next folio

**Description of modification 686:**  
Changing the start button label

Document available on website [alma-alma.fr](http://alma-alma.fr)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	
		<b>Units of measure:</b> Length: mm Angle: degree (° '' ''') Temperature: °C
		Page 24 / 55







# TERMINAL ASSIGNMENT OF THE CONTROL BOX RCT4 VERSION



EQUIPMENT CONNECTED TO THE CONTROL BOX														
Option	Equipement	Cable for information)				Function	Colour or No.	Block	Terminal	Function		Observation		
		N°	CG*	Alma	Type									
	MICROCOMPT+ Serial links	C6			12x0.34 sh	Tx	Vt	BN1	1	Rx	PRINTER	RS485 serial link Embedded computing (EC) Remote control (RC)  RS232 serial link Embedded computing (EC) Remote control (RC)		
Rx						Jn	2		Tx					
0V						Nr	3		0V					
RS485 -						Rs	4		RS485	EC + RC				
RS485 +						Bc	5							
Tx						Bl	10							
Rx						Rg/Bl	11		RS232	EC + RC				
	PRINTER	C1		●	2x1	Rx	Vt	BN2	1	Rx	PRINTER			
Tx						Jn	2		Tx					
0V						Mr	3		0V					
24VDC						Bc	4		24VDC					
	POWER SUPPLY					24VDC		BN3 - Bornier client	1	24VDC	POWER SUPPLY	24VDC truck battery (after battery switch and protected by a fuse)		
					0V		2		0V					
	RC LYNX BELL						5		-	-				
	MOTOR STOP						6		24VDC/0V/CS	MOTOR STOP	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact			
							7		CS					
	PTO						8		24VDC/0V/CS	PTO	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact			
							9		CS					
	HIGH SPEED						10		24VDC/0V/CS	HIGH SPEED	Relay (Configuration 24V, 0V or Free contact) Only used with configuration Free contact			
							11		CS					
	TRUCK TRUNK						12		-	-				
							13		CS	TRUCK TRUNK	Only used with configuration Free contact			
							14		24VDC/0V/CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact)			
	RECEIVER RCT4	C7		●	12G1	24VDC	10		BN3	3	24VDC	SUPPLY CARD AND CRADLE	Power supply for the remote control card and cradle	
0V						11	4			0V				
24VDC						1	BN4	1	24VDC	MICROCOMPT+ POWER SUPPLY AUTHOR.	Fuse			
0V						2		2	0V					
Author.						4		4	EV 3/2NC					
HS						5		5	RELAY			HS	High speed	
PTO						6		6	EV 3/2NC			PTO	Power take off	
Stop						7		7	RELAY			MS	Motor Stop	
DC						8		8	EV 3/2NC			DC	Declutching (or High Speed)	
FV						9		9	EV 3/2NC			FV	Footvalve	
Security						3		BN6	5			RELAY	SECURITY	Safety request
						V/J								

\*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)


**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C


## Pneumatic wiring control box RCT4 version



Label	Input	Output	Function	Observation
Air supply	X		Main supply of the control box + detector for pressure drop	Pressure >1 bar: green warning light Pressure <1 bar: orange warning light. Disable the security management for trunk, pressure drop and customer ARU
	X		Secondary supply of the control box	The 6 bar-calibrated regulator, the 6/4 reducer and the Ø4 coupling are packed in a bag inside the control box
Air from parking brake	X		Air from parking brake	
Exhaust		X	Exhaust	Put a tube L=100mm min. (no muffler)
Emergency stop*		X	Pneumatic emergency stop	
Declutching		X	Declutching actuator (or High speed)	With pneumatic declutching
Footvalve		X	Footvalve opening	
Power take off PTO or Authorisation		X	Power take off or Authorisation	Power take off: leave the plug in place and don't connect any tube in case of electrical control Authorisation: hydraulic control
ARU Emergency stop input	X		Detection of emergency stop requests	ARU are connected in series in a positive safety loop
Trunk	X		Detection of back trunk openings	No air=trunk opened
MS*		X	Timed Master switch	When using the MS pneumatic output
Supply MS*	X		Master switch air supply	When using the MS pneumatic output

\*Unused ports must be plugged.


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 28 / 55






\*Refer to the Cable Glands Installation Instructions

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



5.5. ELECTRICAL WIRING WITH CONTROL BOX AND RC LYNX REMOTE CONTROL



## Terminal assignment of the MICROCOMPT+ power supply board RC LYNX version

Any mass braids and shielding must be connected to the MICROCOMPT+ ground bar

### TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

#### POWER SUPPLY BOARD



EQUIPMENTS CONNECTED TO THE MICROCOMPT+							POWER SUPPLY BOARD			
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function	Observation
		No.	CG*	Alma	Type					
	CONTROL BOX serial links	C6		●	ADR 12x0.34 sh.	Rx	Vt	1	Tx	PRINTER
						Tx	Jn	2	Rx	
						0V	Nr	3	0V	
							Bl	4	Tx	RS232 EC + RC
							Rg/Bl	5	Rx	
						RS485 +	Bc	9	+	Serial link RS485 (RC Lynx) Embedded computing (EC) Remote control (RC)
						RS485 -	Rs	10	-	
						Pulses output +	Rg	22	S	
						Pulses output -	Gr	24	0V	
						Mesur. End	Vi	50	See sub-chapter 2.2	MEASURING END
	TURBINE TRANSMITTER	C3	1/2"NPT		ADR 4x0.34 sh.	12V	Jn	11	12V	TURBINE INPUT
						V1	Mr	12	V1	
						V2	Vt	13	V2	
						0V	Bc	14	0V	
	CONTROL BOX commands	C5		●	12G1	24VDC	1	25	24VDC	POWER SUPPLY 24VDC
						0V	2	26	0V	
						Security	3	72	24VDC	SECURITY
						Author.	4	75	24VDC	AUTHOR.
						HS	5	73	24VDC	HS
						PTO	6	61	24VDC	PTO
						Stop	7	62	24VDC	MS
						DC	8	76	24VDC	DC
	Pt100 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100
						-	Bc	34	-	
						-	Vt	35	-	
				●		-	-	71	0V	Connect 71to 80
						-	-	80	0V	Connect 71to 80

\*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION





## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C








Document available on website [alma-alma.fr](http://alma-alma.fr)




## Electrical wiring control box RC LYNX version

Wiring diagram of the control box RC LYNX version:



### Configuration of switches:

PTO (Power take off), Motor stop (AR MOT), High speed (GD. VIT.), RC LYNX, Truck trunk (COFFRE), Master Switch (M. SW), SW9 and SW13:

		
Linear switching element for relays NC or NO contact	Three-position switch for common contact of the relay: 1 → 24VDC 2 → GND (0V) 3 → CS (Free contact)	SW9 → DEBR. (Declutching) or GD. VIT. (H. speed) for semi-trailer  SW13 → 24V for PTO or AUTOR for semi-trailer

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
 Length: mm  
 Angle: degree (° '' ''')  
 Temperature: °C

# TERMINAL ASSIGNMENT OF THE CONTROL BOX RC LYNX VERSION



EQUIPMENT CONNECTED TO THE CONTROL BOX								CONTROL BOX TERMINAL BLOCKS				
Option	Equipement	Cable for information)				Function	Colour or No.	Block	Terminal	Function		Observation
		N°	CG*	Alma	Type							
	MICROCOMPT+ Serial links	C6			12x0.34 sh	Tx	Vt	BN1	1	Rx	PRINTER	RS485 serial link Embedded computing (EC) Remote control (RC)
						Rx	Jn		2	Tx		
						0V	Nr		3	0V		
						RS485 -	Rs		4	RS485	EC + RC	
						RS485 +	Bc		5			
						Recop +	Rg		6	Recop +	RECOPIE	
						Recop -	Gr		7	Recop -		
						Measur. end	Vi		8		MEASURING END	
						PTO	Mr		9		PTO CONTROL	
						Tx	Bl		10	RS232	EC + RC	RS232 serial link Embedded computing (EC) Remote control (RC)
						Rx	Rg/Bl		11			
	PRINTER	C1		●	2x1	Rx	Vt	BN2	1	Rx	PRINTER	
						Tx	Jn		2	Tx		
						0V	Mr		3	0V		
						24VDC	Bc		4	24VDC		
	POWER SUPPLY					24VDC		BN3 - Bornier client	1	24VDC	POWER SUPPLY	24VDC truck battery (after battery switch and protected by a fuse)
						0V			2	0V		
	POWER SUPPLY REMOTE CONTROL					24VDC			3	24VDC	POWER SUPPLY RC	
	RC LYNX BELL					0V			4	0V		
	MOTOR STOP								6	24VDC/0V/CS	MOTOR STOP	Relay (Configuration 24V, 0V or Free contact)
									7	CS		Only used with configuration Free contact
	PTO								8	24VDC/0V/CS	PTO	Relay (Configuration 24V, 0V or Free contact)
									9	CS		Only used with configuration Free contact
	HIGH SPEED								10	24VDC/0V/CS	HIGH SPEED	Relay (Configuration 24V, 0V or Free contact)
									11	CS		Only used with configuration Free contact
	PTO CONTROL								12	-	-	
	TRUCK TRUNK								13	CS	TRUCK TRUNK	Only used with configuration Free contact
									14	24VDC/0V/CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact)
	MICROCOMPT+ Commands	C5			12G1	24MC	1		BN4	1	24VDC	MICROCOMPT+ POWER SUPPLY
						0MC	2	2		0V		
						Security	3	3		RELAY	SECURITY	Safety request
						Author.	4	4		EV 3/2NC	AUTHOR.	Authorisation
						HS	5	5		RELAY	HS	High speed
						PTO	6	6		EV 3/2NC	PTO	Power take off
						Stop	7	7		RELAY	MS	Motor Stop
						DC	8	8		EV 3/2NC	DC	Declutching (or High Speed)
						FV	9	9		EV 3/2NC	FV	Footvalve
						V/J						
				●		ARU	Bc/Nr	BN5	1			Relier 1 (BN5) à 5 (BN6)
				●		M.SW	-	BN6	5			Relier 1 (BN5) à 5 (BN6)

\*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C




## Pneumatic wiring control box RC LYNX version




Label	Input	Output	Function	Observation
Air supply	X		Main supply of the control box + detector for pressure drop	Pressure >1 bar: green warning light Pressure <1 bar: orange warning light. Disable the security management for trunk, pressure drop and customer ARU
	X		Secondary supply of the control box	The 6 bar-calibrated regulator, the 6/4 reducer and the Ø4 coupling are packed in a bag inside the control box
Air from parking brake	X		Air from parking brake	
Exhaust		X	Exhaust	Put a tube L=100mm min. (no muffler)
Emergency stop*		X	Pneumatic emergency stop	
Declutching		X	Declutching actuator (or High speed)	With pneumatic declutching
Footvalve		X	Footvalve opening	
Power take off PTO or Authorisation		X	Power take off or Authorisation	Power take off: leave the plug in place and don't connect any tube in case of electrical control Authorisation: hydraulic control
ARU Emergency stop input	X		Detection of emergency stop requests	ARU are connected in series in a positive safety loop
Trunk	X		Detection of back trunk openings	No air=trunk opened
MS*		X	Timed Master switch	When using the MS pneumatic output
Supply MS*	X		Master switch air supply	When using the MS pneumatic output

\*Unused ports must be plugged.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE	<u>Units of measure:</u> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 37 / 55

5.6. ELECTRICAL WIRING WITH CONTROL BOX AND ASKW REMOTE CONTROL




## Terminal assignment of the MICROCOMPT+ power supply board ASKW version

Any mass braids and shielding must be connected to the MICROCOMPT+ ground bar

### TERMINAL ASSIGNMENT OF MICROCOMPT+ BOARDS

#### POWER SUPPLY BOARD



EQUIPMENTS CONNECTED TO THE MICROCOMPT+								POWER SUPPLY BOARD				
Option	Equipment	Cable (for information)				Function	Colour or No.	Terminal	Function		Observation	
		No.	CG*	Alma	Type							
	CONTROL BOX serial links	C6		●	ADR 12x0.34 sh.	Rx	Vt	1	Tx	PRINTER	Serial link RS232 Embedded computing (EC) Remote control (RC)	
						Tx	Jn	2	Rx			
						0V	Nr	3	0V			
						Rx	Bl	4	Tx	RS232 EC + RC		Serial link RS485 Embedded computing (EC) Remote control (RC)
						Tx	Rg/Bl	5	Rx			
						RS485 +	Bc	9	RS485+	RS485 EC + RC		
						RS485 -	Rs	10	RS485-			
						Pulses output +	Rg	22	S	PULSES OUTPUT		
						Pulses output -	Gr	24	0V			
						Mesur. End	Vi	53	24VDC	MEASURING END		
PTO control	Mr	58	PTO	PTO CONTROL								
	TURBINE TRANSMITTER	C3	1/2"NPT		ADR 4x0.34 sh.	12V	Jn	11	12V	TURBINE INPUT	Connect the shielding	
						V1	Mr	12	V1			
						V2	Vt	13	V2			
						0V	Bc	14	0V			
	RECEIVER ASKW (PLC) Commands	C5		●	12G1	24VDC	1	25	24VDC	POWER SUPPLY 24VDC	High speed Authorisation Intermediate stop Measuring end	
						0V	2	26	0V			
						HS	3	74	24VDC	HIGH SPEED		
						Author.	4	75	24VDC	AUTHOR.		
						Intermediate stop	5	49	See sub- chapter 2.2	INTERM. STOP		
						Measuring end	6	50	See sub- chapter 2.2	MEASURING END		
	Pt1000 TEMPERATURE PROBE	C2	1/2"NPT		ADR 3x0.6 sh.	+	Jn	33	+	Pt100	Connect the shielding	
						-	Bc	34	-			
						-	Vt	35	-			

\*Refer to the Cable Glands Installation Instruction

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C

Page 39 / 55











## Electrical wiring control box ASKW version


Wiring diagram of the control box ASKW version:



### Configuration of switches:

PTO (Power take off), Motor stop (AR MOT), High speed (GD. VIT.), RC LYNX, Truck trunk (COFFRE), Master Switch (M. SW), SW9 and SW13:

		
<p>Linear switching element for relays NC or NO contact</p>	<p>Three-position switch for common contact of the relay:</p> <p>1 → 24VDC  2 → GND (0V)  3 → CS (Free contact)</p>	<p>SW9 → DEBR. (Declutching)  or GD. VIT. (H. speed)  for semi trailer</p> <p>SW13 → 24V for PTO  or AUTOR for semi trailer</p>

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<p>INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE</p>	<p><b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C</p>
	<p>This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a></p>	<p>Page 42 / 55</p>

# TERMINAL ASSIGNMENT OF THE CONTROL BOX ASKW VERSION



EQUIPMENT CONNECTED TO THE CONTROL BOX								CONTROL BOX TERMINAL BLOCKS				
Option	Equipement	Cable for information)				Function	Colour or No.	Block	Terminal	Function		Observation
		N°	CG*	Alma	Type							
	MICROCOMPT+ Serial links	C6			12x0.34 sh	Tx	Vt	BN1	1	Rx	PRINTER	RS485 serial link Embedded computing (EC) Remote control (RC) RS232 serial link Embedded computing (EC) Remote control (RC)
Rx						Jn	2		Tx			
0V						Nr	3		0V			
RS485 -						Rs	4		RS485	EC + RC		
RS485 +						Bc	5					
Tx						Bl	10		RS232	EC + RC		
Rx						Rg/Bl	11					
	PRINTER	C1		●	2x1	Rx	Vt	BN2	1	Rx	PRINTER	
Tx						Jn	2		Tx			
0V						Mr	3		0V			
24VDC						Bc	4		24VDC			
	POWER SUPPLY					24VDC		BN3 - Bomier client	1	24VDC	POWER SUPPLY	24VDC truck battery (after battery switch and protected by a fuse)
						0V			2	0V		
	POWER SUPPLY REMOTE CONTROL					24VDC			3	24VDC	POWER SUPPLY RC	
	RC LYNX BELL					0V			4	0V		
	MOTOR STOP								5	-	-	
									6	24VDC/0V/CS	MOTOR STOP	Relay (Configuration 24V, 0V or Free contact)
									7	CS	Only used with configuration Free contact	
	PTO								8	24VDC/0V/CS	PTO	Relay (Configuration 24V, 0V or Free contact)
									9	CS	Only used with configuration Free contact	
	HIGH SPEED								10	24VDC/0V/CS	HIGH SPEED	Relay (Configuration 24V, 0V or Free contact)
									11	CS	Only used with configuration Free contact	
	PTO CONTROL								12	-	-	
	TRUCK TRUNK								13	CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact)
									14	24VDC/0V/CS	TRUCK TRUNK	Relay (Configuration 24V, 0V or Free contact)
	RECEIVER ASKW (PLC)	C7		●	12G1	24VDC	10	BN3	3	24VDC	POWER SUPPLY RC	
						0V	11		4	0V		
						24VDC	1		BN4	1	24VDC	
						0V	2	2		0V	AUTHOR.	Authorisation
						Author.	4	4		EV 3/2NC	HS	High speed
						HS	5	5		RELAY	PTO	Power take off
						PTO	6	6		EV 3/2NC	MS	Motor Stop
						Stop	7	7		RELAY	DC	Declutching (or High Speed)
						DC	8	8		EV 3/2NC	FV	Footvalve
						FV	9	9		EV 3/2NC		
						Security	3	BN5	5	RELAY	SECURITY	Safety request
		V/J										

\*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE


This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C

Page 43 / 55

## Electrical wiring ASKW remote control receiver/PLC

### Wiring diagram ASKW receiver/PLC:



ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C

Page 44 / 55

# TERMINAL ASSIGNMENT OF THE ASKW RECEIVER (PLC)



EQUIPMENT CONNECTED TO THE ASKW							TERMINAL BLOCK OF THE PLC FOR ASKW				
Option	Equipement	Cable (for information)				Function	Colour or No.	Block	Terminal	Function	Observation
		N°	CG*	Alma	Type						
	MICROCOMPT+ Commands	C5			12G1	24VDC	1	C7	1	24VDC	Connect to C7
						0V	2	C7	2	0V	Connect to C7
						HS	3		I2	HS	High speed
						Author.	4		I1	AUTHOR.	Authorisation
						Interm. Stop	5	Q1	2	INTERMEDIATE STOP	Intermediate stop
						Measur. End	6	Q2	2	MEASURING END	Measuring end
	CONTROL BOX Commands	C7			12G1	EV Emergency	3	MAQ4	2	SAFETY REQUESTT	Emergency stop
						EV Author.	4		I1	AUTHOR.	Authorisation
						Relay HS	5	MAQ1	2	HS	High speed
						EV PTO	6	MAQ2	15	PTO	CONTINUOUS Power take off
						Relay MS	7	MAQ2	2	PTO	PULSE Power take off
						EV DC	8	Q3	2	MS	Motor Stop
						EV FV	9	MAQ3	2	DC	Declutching
						24VDC	10		I6	FV	Footvalve
									L1		
								Q3	1		
								Q4	1		
								MAQ1	1		
								MAQ2	1	24VDC	BOARD 24V-SUPPLY
								MAQ3	1		
								MAQ4	1		
								MA	L1		
						0V	11		N		
								Q1	1	0V	
								Q2	1		
						Parking brake		MA	N		
									I2	24VDC	Parking brake
									I4		Present: +24VDC Absent: No authorisation

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION




## INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C

Page 45 / 55

# **TERMINAL ASSIGNMENT OF THE ASKW RECEIVER (REMOTE CONTROL)**



EQUIPMENT CONNECTED TO THE ASKW								ASKW REMOTE CONTROL CABLE		
Option	Equipement	Cable (for information)				Terminal	Block	Cable		Observation
		N°	CG*	Alma	Type					
	ASKW PLC					I3		Vt/Nr	CALL/OPTION	
						I4		Bl	DECLUTCHING/STOP	
						I5		Bc	START	Power take off
						I6		Nr/Bc	INTERNAL VALVE	
						I7		Vt	ACTIVATION OF CONTROL-RELAY	
						I8		Rg/Nr	HIGH SPEED	Program in pulse mode
						2	Q4	Rg	24VDC	Protected 10A
						I1	MA	Or	ON/OFF	
						I3				
	MICROCOMPT+	C5		•			2	Nr	GROUND 0V	
	CONTROL BOX	C7		•			2			

\*Refer to the Cable Glands Installation Instructions

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



## **INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE**


This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C


Page 46 / 55





## Pneumatic wiring control box ASKW version



\*Unused ports must be plugged.


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	
		<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
		Page 47 / 55

6. METERING LINE GPL-BALCDocument available on website [alma-aima.fr](http://alma-aima.fr)

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	<b>Units of measure:</b> Length: mm Angle: degree (° '' ''') Temperature: °C
Page 48 / 55		

## 6.1. INSTALLATION AND SEALING RECOMMENDATIONS ADRIANE TURBINE METER

- The identification plate and the led of the pulse emitter(s) shall be visible and accessible.
- The turbine must be installed with respect to the flow direction.
- Put sealing rings each other sides between the turbine and the backflanges.
- Leave an open space all around the turbine in order to ease maintenance.
- Install a 400 $\mu$  filter (mini) on the pipe upstream from the turbine meter.
- After installation or during the commissioning period, if the new or modified pipes have not been perfectly cleaned or pickled and passivated, the turbine should be protected by a honeycomb sieve – max. 1mm mesh. It must be placed between two flanges upstream from the turbine.
- Dimensions: A > 100mm.



- Refer to the certificate written on the identification plate of the measuring system to suit the sealing requirements
- No loose lead wire on the sealing devices



For accuracy class 0.5 and 1.0 measuring systems, the pipes and equipment upstream or downstream the turbine meter must have the same nominal diameter as the meter on a length at least equal to 10 times this diameter upstream and 5 times this diameter downstream.

These lengths can be straight or bent.

It is mandatory that no flowrate adjustment device (e.g. a variable-opening valve) is located upstream at a distance less than 10 times the nominal diameter of the meter: Do not create derivation circuits with sample or bypass, specially make sure that no nozzle is present on this pipe.

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



### INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C

## 7. PRINTER

Technical drawing of the PPN901 Flatbed printer, showing front, side, and top views with dimensions and labels.

**Dimensions:**

- Front view: 180 (width), 190 (height)
- Side view: 101.5 (depth)

**Labels:**

- Switch SW1 (under printer)
- Switch 3 ON
- D-Sub connector 25 pin female
- 24Vdc connector

**Warnings:**

- DO NOT EXPOSE THE PRINTER TO ANY HEAT-SOURCE, AND PROTECT IT FROM VIBRATIONS AND FROM WATER PROJECTIONS.
- IF IT'S NOT IN THE TRUCK CABIN, THE PRINTER MUST BE INSTALLED IN A TIGHT BOX IN ORDER TO FACILITATE INTRODUCTION AND EXTRACTION OF PAPER.

**Technical data:**



- Power supply : 24Vdc  $\pm 10\%$
- Current consumption (at 24V) :
  - Mean : approx. 600mA
  - Peak : approx. 5.5A
- Standby : approx. 100mA
- Temperature :  $+5^{\circ}\text{C}$  to  $+40^{\circ}\text{C}$
- Mass: 1.6 kg

**Service Development**  
 www.alma-alma.fr  
 13127 Vitrolles  
 Code : 6176  
 DEV N° : 907  
 Drawing N° associated with the related CEI file  
 Metro :  
 ATEX:



## 7.1. INSTALLATION RECOMMENDATIONS PRINTER

- The printer must be installed in a tight box and be laid out so as not to obstruct the introduction/extraction of sheet of paper (Dimension D).
- Do not store anything above the printer.
- Leave an open space all around the printer to ease maintenance.
- Dimensions:  $A \geq 50\text{mm}$ ,  $B \geq 100\text{mm}$ ,  $C \geq 120\text{mm}$ .



DO NOT EXPOSE THE PRINTER TO ANY HEAT-SOURCE.  
PROTECT IT FROM VIBRATIONS AND WATER PROJECTIONS.


ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION





## 9. TEMPERATURE PROBE Pt100 – CT1001



- **Mass:** ~350g without thermowell,  
 - **Temperature range:** -20°C to +50°C,  
 - **EX-type examination certificate:** INERIS 04 ATEX 026  
 - **Ex Protection:** Ex ma II T4 Ga

The sensor body is made of bronze color anodized aluminum alloy;  
 The ring and the nut are made of brass.  
 The probe can be mounted either on a ALMA thermowell or on a  
 thimble connection 1/4 "BSP (M10x1 n5).  
 Before installation, lubricate the parts in contact with the thermowell or  
 the boss, to prevent corrosion.


PT100 features:

- 3 wires
- 1/3 DIN


\*ATEX "ma" certification.  
 For installation and use in hazardous areas see Instruction manual

Also available with output connector according to IEC 60947-5-2


Function	Marking on the wire	Color wire
PT100/1	1	Yellow
PT100/2	2	White
PT100/3	3	Green

 <b>Service Development</b> 13127 Vitrolles		PRESENTATION DRAWING <b>DFV042</b>		Description of the amendment N°662 Removal of the apparent 5mm requirement on the wiring							
DEV N° : 949d		Code : 8151		Temperature probe							
Drawing N° associated with the related CET file				CT1001-Pe							
Metro :		949d	PPV042	L	5 / 6	Modified on :	29/03/2019	by	CHR	verified by	CC
ATEX :		Dev N°	Drawing N°	Rev	Folio	Created on :	13/09/2003		BM		BM

Document available on website alma-alma.fr

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	<b>INSTALLATION GUIDE DI 005 EN N</b> <b>LPG-TRONIQUE</b>	
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	
		<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
		Page 53 / 55


9.1. INSTALLATION RECOMMENDATIONS TEMPERATURE PROBE



**REFER TO INSTRUCTION MANUAL**  
(DELIVERED WITH THE EQUIPMENT AND AVAILABLE ON ALMA WEBSITE)


INSTALLATION OF THE TEMPERATURE SENSOR  
ON THE ALMA TURBINE METER:



ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY		
THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION		
	INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE	<b>Units of measure:</b> Length: mm Angle: degree (° ' ") Temperature: °C
	This document is available at <a href="http://www.alma-group.com">www.alma-group.com</a>	Page 54 / 55

## 10. KIT FOR MEASURING SYSTEM IDENTIFICATION PLATE

The identification plate shall be clearly installed, near the associated indicator device, and of easy access in order to be able to read features and to stamp the regulatory marks.



The security screws of the cups (provided by ALMA) must be screwed in the tap of the frame (do not use removable nuts).

ALL RECOMMENDATIONS ARE FOR REFERENCE ONLY

THIS DOCUMENT IS THE PROPERTY OF ALMA. IT CAN BE NEITHER COPIED NOR COMMUNICATED TO ANY THIRD PARTIES WITHOUT ALMA AUTHORIZATION



### INSTALLATION GUIDE DI 005 EN N LPG-TRONIQUE

This document is available at [www.alma-group.com](http://www.alma-group.com)

**Units of measure:**  
Length: mm  
Angle: degree (° ' ")  
Temperature: °C

Page 55 / 55